

## Model: BATTERY line XL

Reference no.: 69-201267-030

Correct use: storage of batteries



|  |                        |
|--|------------------------|
| <b>Product group:</b>  | safety storage cabinet |
| <b>Fire resistance (FR):</b>   | Type 90                |
| <b>Catalogue page:</b>   | 333                    |
| <b>Doors can be opened with minimum effort, design:</b>                            | wing door              |
| <b>Door technology:</b>  | classical              |
| <b>In case of fire, automatic and blockage-free self-closing via thermocouple:</b> | yes                    |
| <b>Outer width [mm]:</b>   | 1195 - (47.05 inch)    |
| <b>Outer depth [mm]:</b>   | 610 - (24.02 inch)     |
| <b>Outer height [mm]:</b>  | 2040 - (80.31 inch)    |
| <b>Base height [mm]:</b>   | 85                     |
| <b>Base version:</b>   | ToeKick                |

|   |                            |
|---|----------------------------|
| <b>Material outer carcass:</b>  | sheet steel, powder-coated |
| <b>Gross weight [kg]:</b>   | 469 - (1033.97 lbs)        |
| <b>Inner width [mm]:</b>  | 1099 - (43.27 inch)        |
| <b>Inner depth [mm]:</b>  | 446 - (17.56 inch)         |
| <b>Inner height [mm]:</b>   | 1830 - (72.05 inch)        |
| <b>Material inner carcass:</b>  | decor panels               |
| <b>Maximum volume of the largest individual container [l]:</b>                          | 44 - (11.62 gal)           |
| <b>Collection volume [l]:</b>   | 49 - (12.94 gal)           |
| <b>Bottom tray interior:</b>  | bottom tray                |
| <b>Number of bottom trays:</b>  | 1                          |
| <b>Perforated sheet interior:</b>   | perforated sheet insert    |
| <b>Number of perforated sheet inserts:</b>  | 1                          |
| <b>Earthing connection according to TRGS 727 available:</b>                             | 1                          |
| <b>Number of earthing connections:</b>  | 2                          |
| <b>Exhaust air connection included:</b>   | NW 75/110                  |
| <b>Standing surface material:</b>   | sheet steel, powder-coated |
| <b>Load-bearing capacity per standing surface with uniformly distributed load [kg]:</b> | 75 - (165.35 lbs)          |
| <b>Adjustment height 1 left [mm]:</b>   | 381.5 - (15.02 inch)       |
| <b>Adjustment height 2 left [mm]:</b>   | 381.5 - (15.02 inch)       |
| <b>Adjustment height 3 [mm]:</b>  | 381.5 - (15.02 inch)       |
| <b>Adjustment height 4 left [inch]:</b>   | 316 - (12.44 inch)         |

|  |                               |
|--|-------------------------------|
| <b>Type-tested by recognised test institutes according to:</b> | DIN EN 14470-1                |
| <b>TÜV-tested according to:</b>                                | DIN EN 14470-1, EK5/AK4 09-10 |
| <b>Further TÜV testing (1):</b>                                | DIN EN 14727                  |
| <b>Declaration of conformity:</b>                              | CE                            |