
Scientific and Healthcare 2023

Next-level cooling solutions

LIEBHERR

Refrigeration and freezing





Comprehensive solutions for refrigeration and freezing with maximum safety

Reliable refrigeration of temperature-sensitive substances poses enormous challenges for the research and healthcare sectors. To help you overcome every one of them, Liebherr offers high-quality refrigerators and freezers combined with innovative monitoring solutions and a comprehensive range of services.

For example, the network connection of refrigerators and freezers with SmartMonitoring guarantees maximum reassurance and a significant reduction in workload. This is also ensured by our high-quality service – from planning and installation to ongoing support.

And, in terms of sustainability, we can boast more than 65 years of expertise and a passion for professional refrigeration and freezing – with unsurpassed energy efficiency, natural refrigerant and extremely long-lasting appliances.

The quality that characterises Liebherr pays off in many ways. On the following pages you can find out how research and healthcare can benefit from our complete solutions.



Contents

The Liebherr Group	6
Brand and quality	8
Sustainability	10
Systems expertise	12
Temperature stability	14
Safety functions	15
Alarms and data storage	16
Cost-efficiency	17
Compliance with standards and directives	18
Overview of SmartMonitoring	20
Liebherr's service promise	22
Series	24
Refrigerators and freezers for laboratories and research	26
Ultra-low temperature freezers	26
ULT Accessories	34
Laboratory refrigerators and freezers with stainless steel inner liner	38
The new generation of appliances for laboratories and research	46
Series	48
Laboratory refrigerators and freezers with plastic inner liner	50
Laboratory refrigerators and freezers with spark-free interior	62
Accessories	72
Pharmaceutical refrigerators	76
Series	78
Pharmaceutical refrigerators compliant with DIN 13277	80
Accessories	90
SmartMonitoring	92



Earthmoving



Material handling



Specialist civil engineering



Mining



Mobile and crawler cranes



Tower Cranes



Concrete technology



Maritime cranes



Aerospace and transportation systems



Gear technology and automation systems



Components



Hotels



Refrigerators and freezers

A tradition of reliability admired the world over.

For more than 70 years Liebherr has offered high-quality products for pioneering industries. With our customers and partners all over the world, we constantly reach new heights.

One big family

The Liebherr Group was established in 1949 by Hans Liebherr. With a history spanning more than 70 years, the family-run company is characterised by stability and reliability. Liebherr is one of the biggest manufacturers of construction equipment and is also successful in many other industries. The Group has a decentralised organisation with around 50,000 employees worldwide and is divided into independently operating business units.

The Group now encompasses 13 product segments – earthmoving machinery, material handling technology, deep foundation machines, mining, mobile and crawler cranes, tower cranes, concrete technology, maritime cranes, aerospace and transportation systems, gear technology and automation systems, refrigerators and freezers, components and hotels – and comprises more than 140 companies across all continents. The holding company of the Group is Liebherr-International AG in Bulle (Switzerland), all of whose shareholders are members of the Liebherr family.



Cutting edge combined with experience: Appliances

The Appliances division was established at the Ochsenhausen site in 1954 and for many years it has played an important part in the development of the Group. For more than 65 years, Liebherr has been a premium manufacturer of innovative refrigerators and freezers for domestic and commercial use. With an annual production of more than 2.2 million appliances, Liebherr is one of Europe's leading suppliers of cooling and freezing appliances. The five production sites in Ochsenhausen (Germany), Lienz (Austria), Radinovo (Bulgaria), Kluang (Malaysia) and Aurangabad (India) form a manufacturing network for refrigerators and freezers that meets all the most up-to-date standards.

Liebherr is active all over the world. With a dense network of sales subsidiaries and offices in Bulgaria, Germany, the UK, Austria, Canada, Malaysia, Russia, Switzerland, Singapore, South Africa and the USA, the refrigeration and freezing specialists ensure that customers receive expert advice and that service and maintenance work is provided professionally on site.

Quality is in our DNA.

Our work is driven by the high demands of our customers worldwide. For more than 65 years, we have been offering high-quality appliances for private and commercial use that meet these high demands, proving their durability and repaying the investment in them.

Specialists in refrigeration and freezing

With outstanding quality, pioneering technologies as well as aesthetic yet user-friendly design, Liebherr sets new standards again and again. How do we do it? By specialising in what we do: developing and manufacturing outstanding refrigerators and freezers, especially for professional use. Research, laboratories and medicine are just some of the areas for whose special requirements our appliances are explicitly designed – with a clear mission: to make your demanding day-to-day work easier with maximum precision and safety.



Cleverly built for maximum safety

Sensitive samples, research materials and preparations allow no room for error with refrigeration. Reliability is crucial. And that's exactly what Liebherr stands for. Liebherr professional appliances have been specifically developed for the challenging requirements of the research, laboratory and medical sectors. With clever design details, high-quality materials and innovative technologies, they provide maximum safety and ease of use.



The Liebherr factor:

Professional refrigerators and freezers

- Specially developed for research, laboratories and medicine
- Safe storage of sensitive substances
- Top quality thanks to elaborate testing procedures
- Complete solution in combination with SmartMonitoring and services

Tested down to the finest detail – and beyond.

From conception through to development and production to marketing, at Liebherr we do everything we can to offer top-quality, innovative products. We test all the mechanical, electronic and refrigeration components for reliable operation, from the development stage onwards. Before we approve a door hinge, for example, it must undergo at least 100,000 opening cycles. You can count on this: your Liebherr appliance will be the professional partner at your side – 24 hours a day, 365 days a year.

Complete responsibility

Responsible use of our resources is our objective and further continuous improvement throughout the product lifecycle is the long-term aim.

This is why we continually develop more environmentally friendly methods for manufacturing more sustainable products – with the familiar Liebherr quality. As well as high energy efficiency, we put a special focus on durability and ensuring that spare parts are available for at least ten years.

Conscientiously developed

We take every aspect of sustainability into account when designing our products. Our product responsibility begins during the development of the appliances and continues with the careful organisation of our production and supply chains. This means the correct choice of materials with regard to recycling as well as minimising the use of energy during production are important factors. During the use phase our almost maintenance-free appliances are characterised by very low energy consumption and low operating costs.

Naturally refrigerated

We were the first to convert our complete range of refrigerators to CFC-free refrigerants and blowing agents. We now only use the natural refrigerants R600, R290 and R170. These are specially designed for highly efficient compressors and also result in lower energy consumption and electricity costs.

Responsibly manufactured

We also make sure we use resources responsibly when manufacturing our appliances. Advanced processes are used to recycle the energy released during production for heating buildings. We also purify the water after the manufacturing process to make sure that it is free of pollutants.



Europe-wide certification

All our European production sites are certified according to the international standards for quality management (ISO 9001), environmental management (ISO 14001) and energy management (ISO 50001).

EcoVadis Gold

We handle the issue of Corporate Responsibility holistically and at all stages of the product life cycle. Our efforts have been awarded gold for 2022 by EcoVadis, the world's leading Corporate Social Responsibility ratings agency. We are proud to be among the top 3% of companies assessed by EcoVadis.



The Liebherr factor:

Environmentally conscious development and production:

- Appliances with very low energy consumption
- Natural refrigerant
- Resource-saving manufacturing processes
- European sites are fully certified
- Gold medal from EcoVadis

Economic success through environmentally aware product design.

The high product quality and energy efficiency of our appliances help you to be economically competitive:

- Low energy consumption
- The savings potential of every component is fully utilised
- Appliance doors close automatically to minimise loss of cold air

Choose refrigeration and freezing from the professionals

Whether in the biotechnology, pharmaceutical research, or in healthcare, the highly demanding work relies on refrigeration that meets the highest standards. With specially developed professional appliances and innovative SmartMonitoring, Liebherr offers solutions for the stringent requirements of the medical and scientific sectors – and good arguments for choosing our systems expertise.

Five good reasons for our outstanding performance.

Discover all the details of SmartMonitoring starting on page 92 and find out how the digital system maximises safety and lightens your workload. Availability varies by country, please contact your Liebherr Account Manager for details.

Reliable temperature stability

Liebherr professional appliances are characterised by outstanding temperature stability. Sensitive vaccines, preparations, samples and medicines are cooled to precise, constant temperatures – even when there are extreme climatic conditions. In addition, SmartMonitoring controls temperature stability and sends alerts in the event of deviations.

Standard safety functions

Liebherr stands for maximum protection of valuable products. Numerous safety functions ensure that the quality of temperature-sensitive substances is constantly assured – as is the quality of your work. If you want maximum certainty, you can use our cloud-based SmartMonitoring solution, with instant notifications for additional peace of mind.

Innovative alarm systems

Research and medicine allow no room for inaccuracy – and that includes storage temperatures. Liebherr professional appliances are equipped with various alarm systems that immediately warn of any deviations and help you to realistically assess critical situations. In addition to the integrated alarm systems, SmartMonitoring also alerts you by text message, email or phone.

Sustainability and economy

Our refrigerators and freezers only use natural refrigerants and are characterised by high efficiency as well as very low energy and operating costs. The outstanding TCO (total cost of ownership) is also down to the long service life, easy care and, not least, the fact that the appliances need hardly any maintenance.

Compliance with standards and directives

Liebherr refrigerators and freezers comply with all the various standards, norms and directives on storage quality, hygiene and safety. In addition, SmartMonitoring documents all the relevant temperature data and automatically generates reports.



Stable temperature – constant quality

Liebherr appliances offer maximum reliability for storing sensitive substances by ensuring constant temperatures. SmartMonitoring additionally monitors the temperature stability and sends an alarm if there are any deviations. This not only maintains the correct climate for storage, but also the value of your stored products.

Precise temperature ranges

Temperature fluctuations must be minimal to ensure that the quality of sensitive substances is preserved. Liebherr refrigerators will not deviate from the set temperature by more than ± 3 °C, and Liebherr freezers will not stray by more than ± 5 °C. This optimally protects the quality of their valuable contents.

Stability is in the air.

The circulating-air refrigeration system and the optimal airflow in the interior keep the temperature stable and ensure that the set temperature is quickly restored after the door has been opened. This means frequent opening of the door during day-to-day use has little effect on temperature stability.



The Liebherr factor:

Consistent refrigeration for reliable storage:

- Temperature setting accurate to a tenth of a degree
- Low tolerance for deviations
- Innovative circulating-air refrigeration system
- Optimal airflow and circulation
- Constant monitoring of the precise storage temperature

Safety as standard

When handling highly sensitive substances, safety has top priority. Whether the risk is unauthorised access or loss of quality – Liebherr protects valuable contents with numerous safety functions and optional SmartMonitoring.

SmartLock: the door that thinks

To prevent products from accidentally entering circulation after an interruption in the cold chain, SmartLock automatically locks the door in the event of an alarm. Only authorised people can unlock it again.

Self locking door: with safety hinges

To make loading, unloading and cleaning easier, the appliance door stays open if opened by more than 90°. If the opening angle is less than 90°, it closes automatically for safety.

Locking systems: individual and secure

Liebherr appliances can be electronically locked and unlocked using an individual PIN code and digital remote control by as many users as you like – without them having to share a key.

+2 °C SafetyDevice: protection from freezing

If the temperature falls below +2 °C due to a malfunction, the SafetyDevice takes control, stabilising the temperature, activating the alarm and protecting the contents from freezing.



SmartMonitoring: extra safety

Liebherr's digital monitoring solution checks and documents the storage temperature and alerts you immediately in the event of deviations for maximum safety in refrigeration and freezing and optimal protection for your valuable contents.

The Liebherr factor:

Integrated safety functions and SmartMonitoring to protect sensitive substances:

- Self-closing door at an opening angle of less than 90°
- Automatic locking in the event of an alarm
- Electronic/mechanical locking systems
- Protection from freezing in the event of malfunctions
- Monitoring, documentation and alarms when required thanks to SmartMonitoring

Checks are good, but alarms are better

Professional refrigerators and freezers together with SmartMonitoring guarantee maximum storage safety through constant temperature monitoring, immediate alarms for uncontrolled fluctuations and recording of critical situations.



LightAlarm:
know at a glance when action is needed

If there is an uncontrolled temperature rise, if a door has been left open or there are any other problems, the interior light of the appliance starts flashing. In the case of glass-door appliances, this quickly reveals where action is needed. With solid-door appliances, the flashing interior warns you to close the door immediately to preserve the storage quality.



Alarm relay:
don't miss any deviations

In the event of an alarm, the responsible control centre is informed immediately, usually through connections to the building control system. You can define in advance which alarms are to be forwarded, as well as set how long forwarding remains active and whether a reminder should be sent after the alarm is acknowledged. This allows you to react immediately in critical situations.



Alarm history:
quality check made easy

In order to be able to evaluate the quality of the stored substances, a clear history of anomalies that have occurred is necessary. The alarm history logs important data such as the date, duration and maximum temperature of the last ten, and can be accessed and reviewed from anywhere.



Integrated data logger:
can be traced back for years

To ensure full traceability, the integrated data logger records the temperature profile, alarm history and service information for up to five years. The stored data can be read directly from the appliance via a USB interface.



SmartMonitoring:
additional digital alarms

If there are deviations in the storage temperature, SmartMonitoring immediately alerts you by email, or by text message or phone (optional). This helps you react before problems arise. In addition, SmartMonitoring documents all relevant temperature data and automatically generates reports. For more details see page 92.

Maximum performance at a minimal cost.

Rising costs increase the requirements that professional refrigerators and freezers must meet. Liebherr scores highly here on every level with sustainably economical appliances.

Ultra-efficient:
good for people and the environment

Rising electricity prices increase the requirements for efficiency in refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of each component. The result is impressive – especially in terms of total cost of ownership.

Outstanding service life:
satisfaction guaranteed

Liebherr appliances are designed for a long service life. Extremely robustly manufactured, they withstand the demands of daily use. This is quality that pays off – for many years to come.

Almost maintenance free:
saves costs, time and aggravation

Liebherr's professional freestanding appliances operate without filters or other components and parts that require regular replacement. They only need to be regularly cleaned and calibrated according to your individual needs.



The Liebherr factor:

Very low energy and total operating costs:

- Energy-efficient
- Extremely long service life
- Almost maintenance-free

Meeting the highest expectations. And the applicable standards and directives.

Hardly any sector has more stringent requirements for the storage of substances than those of research, laboratories and medicine. Liebherr professional appliances are specially developed to meet these extremely strict requirements for aspects such as hygiene and occupational safety.



DIN 13277 compliance

Laboratory and pharmaceutical refrigerators from Liebherr meet all the necessary property and performance criteria to fully comply with DIN 13277.

IEC 61010-2-011 compliance

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always kept safe.

ATEX compliance

Liebherr laboratory appliances conform to EN/IEC 60079-0 / EN-IEC 60079-7 and comply with EU Directive 2014/34/EU ("ATEX Directive"). With an interior classified according to <Ex> II 3 G Ex ec IIC T6 (declared as Zone 22), they are suitable for flammable substances in closed containers that could form explosive atmospheres.

Cleanroom compatibility

A label indicates the cleanroom class in which Liebherr refrigerators and freezers may be operated in accordance with DIN EN ISO 14644 or EU GMP. As a result, no additional risk assessment by the customer for cleanroom suitability is necessary. This saves time and money.

Antimicrobial handle

A benefit for users but a bane for germs, the easy-turn handle mechanism makes opening the door effortless. It also contains special antimicrobial substances that remove the need for regular and time-consuming disinfection. This means the appliance is extremely safe even if many people have access to it.

Recommended cleaning products and disinfectants

Liebherr appliances are designed for a long service life. To maintain them, the manual or separate instructions contain recommendations for cleaning products and disinfectants that have been tested by Liebherr for safe use. This way you can be sure that you are not accidentally harming your appliance when you are trying to take care of it.

Easy-to-clean interior

The inner liner is made of polystyrene: a fully recyclable, robust, and odourless plastic. Manufactured seamlessly from one piece, it has no hidden dirt traps and the large, rounded corners can be cleaned quickly and easily. It's the perfect combination of sustainability and hygiene.

SmartMonitoring

The digital, cloud-based solution from Liebherr helps provide proof of compliance and full documentation of the temperature data (find out more on page 92).



The Liebherr factor:

Designed to meet the strictest standards, norms and directives:

- Suitable for storing sensitive substances in accordance with **DIN 13277**
- Safe operation in accordance with **IEC 61010-2-011**
- ATEX compliant for storing explosive and highly flammable substances
- Cleanroom compatible
- Hygienic and easy-to-clean design
- SmartMonitoring for reliable documentation as proof of temperature compliance

SmartMonitoring: for maximum safety and convenience

SmartMonitoring makes reliable Liebherr appliances even safer and takes protection of valuable contents to a new level. The digital, cloud-based solution automatically and continually monitors and documents the storage temperature – relieving you of a daily task that takes time and attention.

Continuous monitoring

SmartMonitoring constantly and accurately monitors temperature stability – even outside regular working hours, such as at weekends or on public holidays. And it can even do it at different sites for multiple appliances.

Complete documentation

SmartMonitoring documents the temperature and all relevant refrigeration parameters for your stored substances around the clock.

Immediate alarms in the event of deviations

If there are deviations in the storage temperature, you are immediately alerted by email, text message or phone. This way, you can react before problems arise.

Simple commissioning

The new generation of research, laboratory and medical appliances are either already equipped with the SmartModule or can be retrofitted with it and immediately connected to SmartMonitoring. Predecessor models can be easily connected via the SmartCoolingHub. Find out how Liebherr Service can help you take the first steps towards maximum safety.

Discover all the details of SmartMonitoring starting on page 92 and find out how the digital solution maximises safety and lightens your workload. Availability varies by country, please contact your Liebherr Account Manager for details.



Alternatively, go to home.liebherr.com/smartmonitoring

The Liebherr factor:

Maximum safety and convenience with SmartMonitoring:

- An easy, simple and convenient monitoring solution for all network-capable Liebherr appliances
- Constant monitoring of the precise storage temperature
- Frees you up from time-consuming checks and documentation
- Reliable, digital alarm systems
- All relevant data visible at a glance at any time

Endlessly reliable. Take our word for it.

In research, laboratories and medicine, there are ever more jobs to do, and less time to do them in. Liebherr takes some of them off you. Let us lighten your daily workload – with many different services to ensure reliable refrigeration from the professionals.

Delivery right to your door

Liebherr offers you various delivery options. We can deliver your new appliance to the kerbside or take it right in to the place of use and unpack it there. We'll not only take back the packaging for disposal, but also your old appliance if you want.

Installation: it couldn't be quicker

With our installation service, your new appliance is ready in no time to provide you with reliable refrigeration or freezing. Liebherr will not only commission the appliance for you, but also install the digital monitoring solution or other accessories. The availability varies in different countries.

Qualification: let the professionals help

Be on the safe side and save time as well: Liebherr will take care of the time-consuming installation qualification (IQ) and operational qualification (OQ), including the documentation and training. If you want, we can send you the documentation and you can carry out the qualification yourself.

Maintenance: doing it right

Liebherr appliances for research, laboratory and medicine require an impressively low amount of maintenance.

Comprehensive solution for everyday use

Fulfils the highest standards for data protection


Protect your valuable substances

Reliable documentation for proof of temperature compliance

Prevention of damage and loss of quality

More time to concentrate on the essentials

Simple and convenient monitoring solution



Professional delivery service from kerbside to place of installation, including disposal of packaging and old appliances

Fast and professional customer service

Comprehensive expert support for installation qualification (IQ) and operational qualification (OQ)

Large selection of professional appliances for research, medicine and laboratories

Maximum precision and reliable temperature stability

Meets the strict DIN 13277 standard on storage of temperature-sensitive substances such as pharmaceuticals

Two unique series

Whether it's a large research facility or a small laboratory, a doctor's surgery, a nursing home or a pharmacy – our range includes models for every requirement. But however different the appliances are, they all have one thing in common: their first-rate quality.


Performance Perfection

Performance series

All the appliances in the Performance series comply with the safety standard IEC 61010-2-011. In addition, some appliances meet other standards such as the ATEX directive.



Optimal temperature stability




Storage temperature at a glance



LED interior light




Antimicrobial handle with opening mechanism



LightAlarm and SmartLock

Perfection series

The appliances in the Perfection series not only comply with the IEC 61010-2-011 safety standard but also DIN 13277, which specifies requirements for laboratory and medical applications.



Built-in LAN/WiFi interface for SmartMonitoring etc.



ULT freezers – maximum safety and efficiency at ultra-low temperatures

Liebherr ultra-low temperature freezers set new standards in the temperature range from $-40\text{ }^{\circ}\text{C}$ to $-86\text{ }^{\circ}\text{C}$. Not only do they offer unprecedented quality and reliability for storing highly sensitive substances, but also outstanding energy efficiency and ease of use that you will notice every day. Robust, economical and extremely safe, the series of appliances from the experts in freezing for laboratories and research facilities have an impressive number of functions and features.

For optimal protection of your valuable samples, chemicals and research materials. And for the satisfaction of being able to concentrate fully on your work.

The advantages at a glance

SmartMonitoring

The cloud-based digital solution continuously monitors and documents temperatures and alerts you immediately via email, text message or phone if any deviations occur.

Stainless steel workmanship

The interior, shelves and inner doors are made of rust-proof stainless steel and are therefore easy to clean. This enables optimum hygiene.

Shelves

Three stainless steel shelves in the interior, that can be freely adjusted in 24 mm increments, offer flexibility for space-saving storage, tailored to your requirements. You can add more shelves if required.

Serial interfaces

Interfaces for connecting to documentation and monitoring systems such as SmartMonitoring, as well as a volt-free contact for sending alarms to external remote warning systems.



Data recording

There are two feedthroughs (28 mm) on the top and bottom left for installing separate sensors for external monitoring or data recording systems in the interior.

Unloading ramp

No forklift required: the unloading ramp integrated in the packaging helps you easily position the appliance.

Detachable inner door

The detachable inner doors made of rust-proof stainless steel prevent loss of cold air when opening and are also easy to clean.



Door seals

The innovative door seal design, consisting of two all-round seals, makes the door completely airtight when closed. This also helps reduce energy consumption. The seals can be replaced separately and without tools.

Intuitive electronics

The intuitive electronics with integrated real-time clock allow the temperature to be set with an accuracy of one tenth of a degree. The control and display panel is resistant to dirt and easy to clean. Flexible parameter adaptations, such as offset and alarm value settings, allow the appliances to be quickly and easily adapted and qualified for your applications and requirements.



Monitoring system

The 3-stage monitoring system, consisting of integrated alarm notifications for temperature, door or mains electrical faults, upgradable features such as CO₂ emergency refrigeration and online monitoring, ensures optimum protection during storage. In the event of a power failure, integrated 12-volt batteries immediately supply the electronics with power. Notifications are provided in critical situations.

Insulation


The combination of CFC-free polyurethane foam and vacuum-insulated panels ensures the best possible insulation to prevent rapid temperature increases.

Pressure compensation valve

When the door is opened and closed, the air exchange creates a vacuum which makes it difficult to open the door again immediately afterwards. The heated pressure compensation valve quickly equalises the vacuum and the door can be easily opened again after just a few seconds.




SUFsg 5001 MediLine



Quality right down to the smallest detail

Mechanical lock

The mechanical lock protects the stored products from unwanted access. The door is opened with an ergonomic and unbreakable aluminium lever handle.



Minimal temperature fluctuations

In order to maintain the quality of the stored samples, it is important to minimise temperature fluctuations. Liebherr ultra-low temperature freezers are characterised by extremely low fluctuations, both within the appliance and over time.




Low energy consumption

Ultra-low temperature freezers are among the appliances with the highest energy consumption in research facilities. Liebherr ultra-low temperature freezers are some of the most economical models on the market worldwide. In combination with highly insulating vacuum panels, the efficient cooling system allows economical operation, optimum energy savings and therefore low operating costs.




Low heat generation

The efficient cascade cooling system with HC refrigerants generates significantly less heat than previous technologies. This saves costs in the thermal design of the room's air conditioning system. If heat dissipation via the room air conditioning is not possible, water cooling is available as an option.



Connection to documentation and monitoring systems

All the appliances have a volt-free alarm output and an Ethernet interface for remote monitoring. This means the appliances can be connected to SmartMonitoring. In addition, the temperature and alarm records can be read via the integrated USB interface. Optionally, a 4-20 mA output allows the temperature value to be integrated into existing data recording systems.



IQ, OQ, training

From installation qualification (IQ) to operational qualification (OQ) to training, we offer you comprehensive expert help with installation and commissioning. We carry out the various checks for you or set specific parameters for you on request. In addition, we train your staff on site in using the equipment and answer your questions. In our document folder you will also find all the important information about the devices.



Installation service for accessories

Our qualified installation service assists you with professional installation and connection of accessories such as the analogue temperature sensor or CO₂ emergency refrigeration.



SUFSg 7001
MediLine



Gross / net capacity	728 / 700 litre
Exterior dimensions in mm (w / d / h)	1204 / 1082 / 1966
Interior dimensions in mm (w / d / h)	890 / 605 / 1300
Energy consumption in 365 days	2957 kWh
Ambient temperature range	+16 °C to +32 °C
Heat output	1224 kJ/h
Heat output system / Refrigeration system	air cooling / 2-stage cascade system
Refrigerant	R 290 / R 170
Sound power level ¹	47 dB(A)
Voltage / Connection rating	230V~ / 7.0 A
Temperature range	-40 °C to -86 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	Stainless steel
Type of control	LED 7-segment display with buttons
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	LAN (Ethernet)
Data logger	integrated, USB interface
Power failure alarm	immediately upon power failure for 72 hrs
Cooling system	static
Pull-down time +22 °C to -80 °C	450 min
Warm-up time -80 °C to -60 °C / to 0 °C	250 min / 2220 min
Number / maximum number of storage shelves	4 / 13
Adjustable shelves	3
Shelf material	stainless steel
Shelf loading / device	50 kg / 200 kg
Number of racks per shelf	6
Max. number of cryoboxes, 50 mm / 75 mm	528 / 336
Castors	castors with brake at the front, fixed castors at the rear
Access ports	2 x Ø 28 mm
Type of lock	mechanical
Door hinges	right hand hinged, not reversible
Gross / net weight	361 / 313 kg
Accessories	
Racks for cryoboxes	see page 34
Cryoboxes, set of 36	7790038
CO ₂ backup system	7790048
Stainless steel storage shelves	7790050
foamed inner doors	7790127
Cover for mains switch incl. key lock	7790051
4 - 20mA analogue output	7790042
SmartCoolingHub	6125784



SUFSg 7001 ver. H72
MediLine



Gross / net capacity	728 / 700 litre
Exterior dimensions in mm (w / d / h)	1204 / 1082 / 1966
Interior dimensions in mm (w / d / h)	890 / 605 / 1300
Energy consumption in 365 days	2957 kWh
Ambient temperature range	+16 °C to +32 °C
Heat output	1224 kJ/h
Heat output system / Refrigeration system	water-cooled / 2-stage cascade system
Refrigerant	R 290 / R 170
Sound power level ¹	47 dB(A)
Voltage / Connection rating	230V~ / 7.0 A
Temperature range	-40 °C to -86 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	Stainless steel
Type of control	LED 7-segment display with buttons
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	LAN (Ethernet)
Data logger	integrated, USB interface
Power failure alarm	immediately upon power failure for 72 hrs
Cooling system	static
Pull-down time +22 °C to -80 °C	450 min
Warm-up time -80 °C to -60 °C / to 0 °C	250 min / 2220 min
Number / maximum number of storage shelves	4 / 13
Adjustable shelves	3
Shelf material	stainless steel
Shelf loading / device	50 kg / 200 kg
Number of racks per shelf	6
Max. number of cryoboxes, 50 mm / 75 mm	528 / 336
Castors	castors with brake at the front, fixed castors at the rear
Access ports	2 x Ø 28 mm
Type of lock	mechanical
Door hinges	right hand hinged, not reversible
Gross / net weight	361 / 313 kg
Accessories	
Racks for cryoboxes	see page 34
Cryoboxes, set of 36	7790038
CO ₂ backup system	7790048
Stainless steel storage shelves	7790050
foamed inner doors	7790127
Cover for mains switch incl. key lock	7790051
4 - 20mA analogue output	7790042
SmartCoolingHub	6125784

Gross / net capacity	491 / 477 litre
Exterior dimensions in mm (w / d / h)	920 / 1082 / 1966
Interior dimensions in mm (w / d / h)	606 / 605 / 1300
Energy consumption in 365 days	2884 kWh
Ambient temperature range	+16 °C to +32 °C
Heat output	1188 kJ/h
Heat output system / Refrigeration system	air cooling / 2-stage cascade system
Refrigerant	R 290 / R 170
Sound power level ¹	47 dB(A)
Voltage / Connection rating	230V~ / 7.0 A
Temperature range	-40 °C to -86 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	Stainless steel
Type of control	LED 7-segment display with buttons
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	LAN (Ethernet)
Data logger	integrated, USB interface
Power failure alarm	immediately upon power failure for 72 hrs
Cooling system	static
Pull-down time +22 °C to -80 °C	360 min
Warm-up time -80 °C to -60 °C / to 0 °C	230 min / 2160 min
Number / maximum number of storage shelves	4 / 13
Adjustable shelves	3
Shelf material	stainless steel
Shelf loading / device	50 kg / 200 kg
Number of racks per shelf	4
Max. number of cryoboxes, 50 mm / 75 mm	352 / 224
Castors	castors with brake at the front, fixed castors at the rear
Access ports	2 x Ø 28 mm
Type of lock	mechanical
Door hinges	right hand hinged, not reversible
Gross / net weight	308 / 254 kg
Accessories	
Racks for cryoboxes	see page 34
Cryoboxes, set of 36	7790038
CO ₂ backup system	7790048
Stainless steel storage shelves	7790049
foamed inner doors	7790070
Cover for mains switch incl. key lock	7790051
4 - 20mA analogue output	7790042
SmartCoolingHub	6125784



SUFSg 5001
MediLine



Gross / net capacity	491 / 477 litre
Exterior dimensions in mm (w / d / h)	920 / 1082 / 1966
Interior dimensions in mm (w / d / h)	606 / 605 / 1300
Energy consumption in 365 days	2884 kWh
Ambient temperature range	+16 °C to +32 °C
Heat output	1188 kJ/h
Heat output system / Refrigeration system	air cooling / 2-stage cascade system
Refrigerant	R 290 / R 170
Sound power level ¹	47 dB(A)
Voltage / Connection rating	230V~ / 7.0 A
Temperature range	-40 °C to -86 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	Stainless steel
Type of control	LED 7-segment display with buttons
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	LAN (Ethernet)
Data logger	integrated, USB interface
Power failure alarm	immediately upon power failure for 72 hrs
Cooling system	static
Pull-down time +22 °C to -80 °C	360 min
Warm-up time -80 °C to -60 °C / to 0 °C	230 min / 2160 min
Number / maximum number of storage shelves	4 / 13
Adjustable shelves	3
Shelf material	stainless steel
Shelf loading / device	50 kg / 200 kg
Number of racks per shelf	4
Max. number of cryoboxes, 50 mm / 75 mm	352 / 224
Castors	castors with brake at the front, fixed castors at the rear
Access ports	2 x Ø 28 mm
Type of lock	mechanical
Door hinges	right hand hinged, not reversible
Gross / net weight	308 / 254 kg
Accessories	
Racks for cryoboxes	see page 34
Cryoboxes, set of 36	7790038
CO ₂ backup system	7790048
Stainless steel storage shelves	7790049
foamed inner doors	7790070
Cover for mains switch incl. key lock	7790051
4 - 20mA analogue output	7790042
SmartCoolingHub	6125784

SUFSg 5001 ver. H72
MediLine



Gross / net capacity	491 / 477 litre
Exterior dimensions in mm (w / d / h)	920 / 1082 / 1966
Interior dimensions in mm (w / d / h)	606 / 605 / 1300
Energy consumption in 365 days	2884 kWh
Ambient temperature range	+16 °C to +32 °C
Heat output	1188 kJ/h
Heat output system / Refrigeration system	water-cooled / 2-stage cascade system
Refrigerant	R 290 / R 170
Sound power level ¹	47 dB(A)
Voltage / Connection rating	230V~ / 7.0 A
Temperature range	-40 °C to -86 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	Stainless steel
Type of control	LED 7-segment display with buttons
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	LAN (Ethernet)
Data logger	integrated, USB interface
Power failure alarm	immediately upon power failure for 72 hrs
Cooling system	static
Pull-down time +22 °C to -80 °C	360 min
Warm-up time -80 °C to -60 °C / to 0 °C	230 min / 2160 min
Number / maximum number of storage shelves	4 / 13
Adjustable shelves	3
Shelf material	stainless steel
Shelf loading / device	50 kg / 200 kg
Number of racks per shelf	4
Max. number of cryoboxes, 50 mm / 75 mm	352 / 224
Castors	castors with brake at the front, fixed castors at the rear
Access ports	2 x Ø 28 mm
Type of lock	mechanical
Door hinges	right hand hinged, not reversible
Gross / net weight	308 / 254 kg
Accessories	
Racks for cryoboxes	see page 34
Cryoboxes, set of 36	7790038
CO ₂ backup system	7790048
Stainless steel storage shelves	7790049
foamed inner doors	7790070
Cover for mains switch incl. key lock	7790051
4 - 20mA analogue output	7790042
SmartCoolingHub	6125784

Ultra-low temperature freezers

Racks for cryoboxes

Convenient and temperature-resistant storage systems for well-organised sample storage. Available as aluminium or stainless steel side-access racks for 5x4 or 6x4 50 mm boxes and as stainless steel front-access drawer racks for 5x4 or 6x4 50 mm boxes.

Maximum Loading SUFsg 5001: 8x Rack 5x4 + 8x Rack 6x4 = 352 boxes x 81 pcs. 2mL samples.

Maximum Loading SUFsg 7001: 12x Rack 5x4 + 12x Rack 6x4.



Aluminium side-access rack 5x4	7790003	Stainless steel side-access rack 5x4	7790027
Aluminium side-access rack 6x4	7790014	Stainless steel side-access rack 6x4	7790028
Aluminium side-access rack 5x4 + cryoboxes	7790015	Stainless steel front-access rack 5x4 + drawers	7790031
Aluminium side-access rack 6x4 + cryoboxes	7790025	Stainless steel front-access rack 6x4 + drawers	7790032
Stainless steel side-access rack 5x4 + cryoboxes	7790029	Stainless steel front-access rack 5x4 + cryoboxes + drawers	7790033
Stainless steel side-access rack 6x4 + cryoboxes	7790030	Stainless steel front-access rack 6x4 + cryoboxes + drawers	7790036




Foamed inner doors

The foamed inner doors provide the best possible insulation and temperature stability, ensuring efficient cooling and low power consumption.



Cover for mains switch incl. key lock

Protection against unintended disconnection or manipulation of the mains switch.



4-20mA analogue output

The 4-20mA interface displays the interior temperature as a current value, which for example can be imported into an independent system for recording or checking the internal temperature.



Cryoboxes

The set contains 36 durable and temperature-resistant cryoboxes made from water-repellent cardboard, with fixed 9x9 grid, for safe storage and transport of valuable samples.



CO₂ backup system

The CO₂ backup system ensures that the cooling of the stored samples continues at reduced temperatures for up to 72 hours in the event of a power failure. The CO₂ bottle is not part of the accessory.



Stainless steel storage shelves

Additional robust stainless steel shelves for flexible and individual partitioning of the interior at 24 mm increments.



SmartCoolingHub

The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.



RS485 connection cable

The ModBUS-compatible 5-metre cable connects your appliance to the SmartCoolingHub. If you want to connect several appliances, you need an additional cable for each appliance.



Research and laboratory appliances – for maximum precision and safety

Hardly any sector has more stringent requirements for refrigerators and freezers than those of laboratories and research. Liebherr meets them with a specifically developed range and a new generation of appliances.

Sensitive substances are reliably stored at precise temperatures and additionally protected by integrated alarm systems. Maximum efficiency ensures low consumption, while durable materials and maintenance-free components guarantee minimal operating costs. The comprehensive range is user-friendly and easy to connect in a network – such as Liebherr SmartMonitoring.

Discover typical Liebherr quality that will pay off for years and lighten your daily workload.

The advantages at a glance

The LKPv 1420, LKPv 1423 and LGPv 1420 models can be taken apart and reassembled for easier transport. This must always be done by a trained technician. Contact Liebherr Sales for more information.

Integrated data memory

The minimum and maximum values can be stored for up to 41 days, and the last three power failures and temperature alarms can be recorded and retrieved.

Emergency battery

If there is a power failure, the electronics are immediately powered by an integrated 12 V battery. This means the integrated memory can carry on logging the interior temperatures without interruption for another 72 hours.



External temperature sensor

The laboratory appliances have a feedthrough (7.0 mm diameter) in the ceiling of the appliance for fitting a temperature sensor in the interior.

Stainless steel workmanship

The smooth interior made of chrome-nickel steel is easy to clean and ensures optimal hygiene.

Space-saving

To save space and increase the interior capacity, functional components such as fans and evaporators are located outside the refrigerator compartment.



LKPv 6520 MediLine

Pressure compensation valve

When the door of a refrigerator or freezer is opened and closed, the exchange of air creates a vacuum that makes it difficult to open the door again immediately afterwards. The pressure compensation valve quickly equalises the vacuum so that the door can be easily opened again.

SmartMonitoring

The cloud-based digital solution continuously monitors and documents temperatures and alerts you immediately via email, text message or phone if any deviations occur.

Integrated alarm systems

If the door is open for longer than one minute, a visual and audible alarm is generated. The temperature and power failure alarm indicates that the temperature is too high or too low, and also warns in the event of power failures.

Dynamic cooling system

The dynamic cooling system with double ventilation combined with optimal airflow ensures maximum temperature stability in the interior.



90° door arrester

For convenient use, the practical door remains open at 90° and is self-closing at less than 60°.

Castors


The LKPv and LGPv ranges come with castors as standard to allow versatile use according to the available space, as well as easy cleaning, even under the appliances.



Split-door appliances

Quick access, minimal loss of cold air, longer-lasting product quality. Split-door appliances are ideal for use in the pharmaceutical industry or laboratories when the door has to be frequently opened. Frequently used samples and preparations can be kept in the upper section for quick access, while there is plenty of room below for items and raw materials that are required less often. Thanks to the split doors with their self-closing mechanism, only a little cold air escapes on opening, and this helps maintain a stable temperature and preserve the quality of the stored items for the long term.

Quality right down to the smallest detail



Maximum temperature stability


The dynamic cooling system with double ventilation ensures maximum temperature stability in the interior. Very short defrost cycles allow the interior temperature to be kept almost constant during the defrost phases. All the laboratory appliances are designed for temperature stability and consistency according to EN 60068-3.

Advantage of hot gas defrosting
Reduces the time when the temperature is increased

30 min Electric defrosting	10 min Hot gas defrosting
-------------------------------	------------------------------

Energy-efficient hot gas defrosting

Timed and on-demand hot gas defrosting allows very short defrosting times. To additionally improve temperature stability during defrosting, the internal temperature is slightly lowered shortly beforehand to create a reserve of cold air.



Accurate 1-point calibration

The laboratory appliances with electronic controls have a 1-point calibration function for extremely accurate temperature control. This allows compensation between the set temperature and the actual interior temperature. The correction value can be adjusted in increments of 0.1 K.



Integrated electronics

The intuitive controller with integrated real-time clock allows the temperature to be set to 1/10°C accuracy. The keypad is resistant to dirt and easy to clean – to meet the most stringent hygiene requirements of the laboratory.



Easily accessible refrigeration components

The refrigeration components are easily accessible, located in the upper part of the machinery compartment to significantly increase the capacity of the interior. The front can be easily lifted up to facilitate cleaning or servicing. When opened by more than 45 ° it can be completely detached.



External temperature and alarm documentation

The laboratory appliances are equipped with an RS 485 serial interface – which means that up to 20 appliances can be connected via the SmartCoolingHub to a network and the SmartMonitoring system, or used with an external documentation and alarm system. The appliances also have a volt-free contact to relay alarms to an external remote warning system.



LKPV 1423
MediLine



LKPV 1420
MediLine



Gross / net capacity	1397 / 980 litre
Exterior dimensions in mm (w / d / h)	1430 / 830 / 2160
Interior dimensions in mm (w / d / h)	1236 / 650 / 1500
Energy consumption in 365 days ¹	820 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	515 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	3.8 °C / 3.9 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Adjustable shelves	8
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	1236 / 640
Shelf loading	60 kg
Castors	castors with brake at the front, castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	left hand / right hand
Gross / net weight	267 / 224 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590639
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



LKPV 8420
MediLine



LKPV 6523
MediLine



LKPV 6520
MediLine



LKPV 6527
MediLine



Gross / net capacity	855 / 629 litre
Exterior dimensions in mm (w / d / h)	790 / 980 / 2160
Interior dimensions in mm (w / d / h)	620 / 850 / 1550
Energy consumption in 365 days ¹	603 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	430 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	2.1 °C / 1.8 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	620 / 800
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	175 / 145 kg
Accessories	
Shelf, plastic-coated	7113643
U-shaped trayslide, right	9005089
U-shaped trayslide, left	9005077
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	617 / 430 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1500
Energy consumption in 365 days ¹	571 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	345 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	0 °C to +16 °C
Gradient ² / max. fluctuation ³	2.0 °C / 1.6 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	164 / 138 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	602 / 430 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1500
Energy consumption in 365 days ¹	497 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	300 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	1.8 °C / 1.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	154 / 128 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	598 / 429 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1550
Energy consumption in 365 days ¹	688 kWh
Ambient temperature range	+10 °C to +40 °C
Heat output	345 kJ/h
Refrigerant	R 290
Sound power level	58 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-2 °C to +16 °C
Gradient ² / max. fluctuation ³	1.8 °C / 1.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Access ports	1 x Ø 7 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	155 / 130 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



LGPv 1420
MediLine



LGPv 8420
MediLine



LGPv 6520
MediLine



LGPv 6527
MediLine



Gross / net capacity	1366 / 980 litre
Exterior dimensions in mm (w / d / h)	1430 / 830 / 2160
Interior dimensions in mm (w / d / h)	1236 / 650 / 1550
Energy consumption in 365 days¹	2654 kWh
Ambient temperature range	+10 °C to +40 °C
Refrigerant	R 290
Sound power level	60 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-9 °C to -26 °C
Gradient³ / max. fluctuation⁴	4.3 °C / 6.7 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	8
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	1236 / 640
Shelf loading	60 kg
Castors	castors with brake at the front, castors at the rear
Handle	full-length integrated handle
Type of lock	mechanical
Door hinges	left hand / right hand
Gross / net weight	254 / 209 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590639
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	855 / 629 litre
Exterior dimensions in mm (w / d / h)	790 / 980 / 2160
Interior dimensions in mm (w / d / h)	620 / 850 / 1550
Energy consumption in 365 days¹	1739 kWh
Ambient temperature range	+10 °C to +40 °C
Refrigerant	R 290
Sound power level	60 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-9 °C to -35 °C ²
Gradient³ / max. fluctuation⁴	4.5 °C / 5.7 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	620 / 800
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	182 / 150 kg
Accessories	
Shelf, plastic-coated	7113643
U-shaped trayslide, right	9005089
U-shaped trayslide, left	9005077
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	602 / 430 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1550
Energy consumption in 365 days¹	1367 kWh
Ambient temperature range	+10 °C to +40 °C
Refrigerant	R 290
Sound power level	60 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-9 °C to -35 °C ²
Gradient³ / max. fluctuation⁴	2.9 °C / 3.6 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	162 / 136 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

Gross / net capacity	598 / 429 litre
Exterior dimensions in mm (w / d / h)	700 / 830 / 2160
Interior dimensions in mm (w / d / h)	533 / 650 / 1550
Energy consumption in 365 days¹	2019 kWh
Ambient temperature range	+10 °C to +40 °C
Refrigerant	R 290
Sound power level	60 dB(A)
Voltage / Connection rating	220 - 240V~ / 4.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	-9 °C to -35 °C ²
Gradient³ / max. fluctuation⁴	2.9 °C / 3.6 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	304-grade stainless steel
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for 72 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	4
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	533 / 650
Shelf loading	60 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	full-length integrated handle
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	160 / 134 kg
Accessories	
Shelf, plastic-coated	7112393
U-shaped trayslide, right	9001761
U-shaped trayslide, left	9001757
Foot pedal opener	9590659
SmartCoolingHub	6125784
Product temperature sensor	9590407
Side-by-Side set	9901947

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.
² The temperature range is valid at a maximum ambient temperature of +30°C

³ Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
⁴ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



The new generation of appliances for laboratories and research – safety redefined

Constant temperatures are essential when storing sensitive substances. This especially applies to work in laboratories, where even the slightest deviations can jeopardise the quality of research results. This is why Liebherr has developed new refrigerators and freezers specifically for this sector, combining maximum refrigeration performance with optimum temperature stability. Innovative safety features with monitoring and alarm functions offer all-round protection from all kinds of incident and malfunction.

The next generation of appliances also set new standards in terms of energy efficiency and total cost of ownership. On the next few pages we present the latest results of research and development by the refrigeration specialists at Liebherr and show how they can benefit safety in your laboratory.

The advantages at a glance

Min./max. temperature log

The min./max. temperature log stores the minimum and maximum interior temperatures and shows on the display whether the storage temperatures were within the tolerance limits.

+2 °C SafetyDevice

If the temperature falls below +2 °C due to a malfunction, the SafetyDevice takes control, stabilising the temperature, activating the alarm and protecting the contents from freezing.

Power failure alarm

If a malfunction occurs, an integrated battery provides a visual and audible alarm and takes over the power supply. As soon as the power is restored, the time of failure and the maximum temperature reached are displayed.

LightAlarm

In the event of an uncontrolled temperature rise or other problems, the interior light of the appliance starts flashing. This visually shows when action is needed.

Feedthrough for external sensors

An integrated opening allows a separate sensor to be connected for additional temperature monitoring without having to drill holes or break the door seal.

Integrated data logger

The integrated logger records the temperature profile, alarm history and service information for up to five years. The data can be read out directly from the appliance via the USB interface.



SRFvh 4011 Perfection

The equipment details shown depend on the model; the description for the respective model applies.



Mechanical lock

Liebherr professional appliances are equipped with a mechanical lock and two keys. This ensures that unauthorised persons cannot access your valuable and sensitive stored goods.

SmartMonitoring

The cloud-based digital solution continuously monitors and documents temperatures and alerts you immediately via email, text message or phone if any deviations occur.

Integrated WiFi/LAN interface

The integrated WiFi/LAN interface enables you to easily connect your appliances with Liebherr SmartMonitoring or existing local systems.

Easy-to-clean interior

The inner liner made of fully recyclable, robust and odourless polystyrene is manufactured in one piece without joints. This makes it quick and easy to clean the large, rounded corners.



Replaceable door seal

Save time and money: the insertable Liebherr door seals are easy to change. If a seal is damaged, you can replace it yourself without any tools. Contact Liebherr Customer Service to purchase replacements.



Self-closing door < 90°

To make loading, unloading and cleaning easier, the appliance door stays open if opened by more than 90°. If the opening angle is less than 90°, it closes automatically for safety.

Quality right down to the smallest detail



Antimicrobial handle with opening mechanism

The smooth-turning handle contains special antimicrobial substances that make it particularly hygienic. Regular and time-consuming disinfection is not necessary.



Grid shelf with pull-out stop

Corrosion-free grid shelves made of coated steel guarantee a secure hold, constant air circulation and good temperature stability. A pull-out stop prevents them from accidentally sliding out.



Ultra Efficient

Ultra-efficient

Rising electricity prices are increasing the demands on the efficiency of refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of every component. The result is impressive – especially in terms of total operating costs.

Vertical LED lighting

Vertical LED lighting provides optimal illumination of the interior over the entire height of the appliance. Thanks to the perfect overview on all levels, the required substance is immediately at hand, the door can be quickly closed again, and the interior temperature remains stable. This saves you time looking for things – and above all energy costs.



±3 °C temperature stability

Temperature fluctuations must be minimal to ensure that the quality of sensitive substances is preserved. Liebherr Laboratory refrigerators have an impressive maximum deviation of just ±3 °C from the set temperature. This not only maintains the storage climate, but also the value of your stored goods.



DIN 13277 compliance

Laboratory and pharmacy refrigerators from Liebherr meet all the necessary equipment and performance criteria to fully comply with DIN 13277. DIN 13277 defines the requirements and test specifications for refrigerators and freezers used in laboratories and for storing medicinal products.



IEC 61010-2-011 standard

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always safe.



SRFvh 5511
Perfection



Gross / net capacity	588 / 440 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1793
Interior dimensions in mm (w / d / h)	606 / 536 / 1460
Energy consumption in 365 days ¹	360 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	475 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.3 °C / 2.0 °C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	Vertical LED light strip recessed in left wall with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	606 / 536
Shelf loading / device	60 kg / 300 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	mechanical / right, reversible on site
Gross / net weight	111 / 98 kg
Accessories	
Shelf, plastic-coated	7113310
Base grid	7113314
Glass shelf	9291929
Scanner rail	7435210
Castors Ø 80 mm	9086926
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request



SRFvh 5501
Perfection



Gross / net capacity	558 / 441 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1793
Interior dimensions in mm (w / d / h)	606 / 536 / 1460
Energy consumption in 365 days ¹	171 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	246 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	2.2 °C / 1.7 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED lighting column, left
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	606 / 536
Shelf loading / device	60 kg / 300 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	mechanical / right, reversible on site
Gross / net weight	94 / 80 kg
Accessories	
Shelf, plastic-coated	7113310
Base grid	7113314
Glass shelf	9291929
Scanner rail	7435210
Castors Ø 80 mm	9086926
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request



SRFvh 4011
Perfection



Gross / net capacity	420 / 297 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1660
Energy consumption in 365 days ¹	389 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	463 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.0 °C / 2.4 °C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	Vertical LED light strip recessed in left wall with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	mechanical / right, reversible on site
Gross / net weight	86 / 80 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request



SRFvh 4001
Perfection



Gross / net capacity	394 / 298 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1660
Energy consumption in 365 days ¹	172 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	250 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	2.4 °C / 2.2 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED lighting column, left
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	mechanical / right, reversible on site
Gross / net weight	71 / 65 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



SRFvg 5511
Performance



SRFvg 5501
Performance



SRFvg 4011
Performance



SRFvg 4001
Performance



SRFvg 3511
Performance



SRFvg 3501
Performance



Gross / net capacity	588 / 440 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	606 / 536 / 1442
Energy consumption in 365 days¹	433 kWh
Ambient temperature range	+10°C to +35°C
Heat output	542 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	3.8°C / 3.2°C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	606 / 536
Shelf loading / device	60 kg / 300 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	106 / 96 kg
Accessories	
Shelf, plastic-coated	7113310
Base grid	7113314
Glass shelf	9291929
Perforated metal shelf	
Scanner rail	7435210
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	558 / 441 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	606 / 536 / 1460
Energy consumption in 365 days¹	250 kWh
Ambient temperature range	+10°C to +35°C
Heat output	317 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	3.9°C / 3.0°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	606 / 536
Shelf loading / device	60 kg / 300 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	87 / 80 kg
Accessories	
Shelf, plastic-coated	7113310
Base grid	7113314
Glass shelf	9291929
Perforated metal shelf	
Scanner rail	7435210
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803590
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	420 / 297 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1642
Energy consumption in 365 days¹	431 kWh
Ambient temperature range	+10°C to +35°C
Heat output	542 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	5.9°C / 3.4°C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	89 / 82 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803588
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	394 / 298 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1660
Energy consumption in 365 days¹	245 kWh
Ambient temperature range	+10°C to +35°C
Heat output	321 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	4.6°C / 2.2°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	71 / 66 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803588
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	367 / 260 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1684
Interior dimensions in mm (w / d / h)	460 / 423 / 1442
Energy consumption in 365 days¹	393 kWh
Ambient temperature range	+10°C to +35°C
Heat output	471 kJ/h
Refrigerant	R 600a
Sound power level	48 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	3.6°C / 3.2°C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 180 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	82 / 76 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803588
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	344 / 261 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1684
Interior dimensions in mm (w / d / h)	460 / 423 / 1460
Energy consumption in 365 days¹	226 kWh
Ambient temperature range	+10°C to +35°C
Heat output	288 kJ/h
Refrigerant	R 600a
Sound power level	48 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	5.0°C / 3.1°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	4 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 180 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	66 / 60 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803588
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Gross / net capacity	420 / 297 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1642
Energy consumption in 365 days¹	431 kWh
Ambient temperature range	+10°C to +35°C
Heat output	542 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	5.9°C / 3.4°C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Retrofittable
Interface	WiFi/LAN (optional)
Interior light	LED ceiling light strip with separate switch
Adjustable shelves / Shelf material	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	89 / 82 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid	7113312
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Evaporator cover	9803588
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.


³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

Quality right down to the smallest detail



LED front lighting


The LED front lighting provides optimal illumination of the drawers even in dark environments. Thanks to the perfect overview, the desired substance is immediately at hand, the door can be quickly closed again, and the interior temperature remains stable. For low consumption and lower energy costs.



No Frost

NoFrost technology

Liebherr professional laboratory appliances no longer need manual defrosting. Any moisture that occurs is bound by the fan-assisted cooling, and when necessary, defrosting phases remove any remaining moisture particles from of the interior – for convenient, safe, and ice-free storage.



Ultra Efficient

Ultra-efficient

Rising electricity prices are increasing the demands on the efficiency of refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of every component. The result is impressive – especially in terms of total operating costs.



±5 °C temperature stability

Sensitive substances cannot be subjected to large deviations from the set storage temperature. Liebherr freezers guarantee a temperature fluctuation of no more than ±5 °C, so that the valuable goods you store in them are optimally protected and their quality is preserved.



DIN 13277 compliance

Laboratory and pharmacy refrigerators from Liebherr meet all the necessary equipment and performance criteria to fully comply with DIN 13277. DIN 13277 defines the requirements and test specifications for refrigerators and freezers used in laboratories and for storing medicinal products.



IEC 61010-2-011 standard

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always safe.



SFFvh 5501
Perfection



SFFsg 5501
Performance



SFFsg 4001
Performance



Gross / net capacity	472 / 257 litre	499 / 394 litre	316 / 242 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1793	747 / 769 / 1684	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	603 / 510 / 1118	588 / 523 / 1388	403 / 408 / 1588
Energy consumption in 365 days¹	540 kWh	501 kWh	468 kWh
Ambient temperature range	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C
Refrigerant	R 290	R 290	R 290
Sound power level	55 dB(A)	49 dB(A)	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A	220 - 240V~ / 2.0 A	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic	static / manual	static / manual
Temperature range	-9 °C to -35 °C	-9 °C to -30 °C	-9 °C to -30 °C
Gradient² / max. fluctuation³	5.5 °C / 4.4 °C	6.0 °C / 2.9 °C	5.7 °C / 2.5 °C
External cabinet finish	steel / white	steel / white	steel / white
Door material	steel	steel	steel
Internal liner material	commercial grade moulded polystyrol	commercial grade moulded polystyrol	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display	monochrome display, touch buttons	monochrome display, touch buttons
Power failure alarm	immediately upon power failure for at least 12 hrs	when mains power return	when mains power return
Fault: warning signal	visual and audible	visual and audible	visual and audible
Volt-free alarm contact	yes	yes	yes
Connectivity type / Connectivity solution	SmartModule / Integrated, removable	SmartModule / Retrofittable	SmartModule / Retrofittable
Interface / Data logger	WiFi/LAN / integrated, USB interface	WiFi/LAN (optional) / -	WiFi/LAN (optional) / -
Interior light	LED		
Adjustable shelves / Shelf material	4 / wire shelves plastic-coated	4 / wire shelves plastic-coated	5 / wire shelves plastic-coated
Usable shelf area in mm (w / d)	603 / 510	588 / 523	403 / 408
Shelf loading / device	60 kg / 300 kg	60 kg / 300 kg	45 kg / 270 kg
Castors	castors with brake at the front, fixed castors at the rear		
Drawers / Number of baskets	6 / 2		
Handle	Antimicrobial handle with opening mechanism	Antimicrobial handle with opening mechanism	Antimicrobial handle with opening mechanism
Type of lock / Door hinges	mechanical / right, reversible on site	mechanical / right, reversible on site	mechanical / right, reversible on site
Gross / net weight	114 / 104 kg	94 / 80 kg	81 / 76 kg
Accessories			
Shelf, plastic-coated	7112590		
Glass shelf / Full-depth drawer		9293495 / 9797881	9293499 / -
Short bottom basket / Standard full-depth basket	- / 9141791	9141004 / 9141791	
Castors Ø 80 mm / Ø 100 mm	9086926 / -	9086926 / 9080023	9086926 / 9080023
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924	9080022 / 9086924	9080022 / 9086924
Additional lock barrels (up to 5)	on request	on request	on request
Side-by-Side set	on request	on request	on request
Product sensor (PT 1000)	6942678		
SmartModule		6145269	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



LKUv 1613
MediLine



LKUv 1610
MediLine



Gross / net capacity	152 / 132 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days ¹	369 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	5.1 °C / 4.9 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	45 / 43 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
Evaporator cover, white	9590523
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	142 / 133 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days ¹	273 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	4.3 °C / 4.6 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	40 / 37 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
Evaporator cover, white	9590523
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



LCv 4010
MediLine



Gross / net capacity	fridge compartment
Gross / net capacity	freezer compartment
Exterior dimensions in mm (w / d / h)	
Interior dimensions in mm (w / d / h)	fridge compartment
Interior dimensions in mm (w / d / h)	freezer compartment
Energy consumption in 365 days ¹	
Ambient temperature range	
Refrigerant	
Sound power level	
Voltage / Connection rating	
Cooling system	fridge / freezer comp.
Defrost	fridge / freezer comp.
Temperature range	fridge / freezer comp.
Gradient ²	fridge / freezer comp.
Max. fluctuation ³	fridge / freezer comp.
External cabinet finish	
Door material	
Internal liner material	
Type of control	
Power failure alarm	
Fault: warning signal	
Volt-free alarm contact	
Connectivity type	
Connectivity solution	
Interface	
Adjustable shelves	fridge compartment
Shelf material	fridge / freezer comp.
Usable shelf area in mm (w / d)	fridge compartment
Shelf loading	fridge / freezer comp.
Drawers	freezer compartment
Handle	
Type of lock	
Door hinges	
Gross / net weight	
Accessories	
Shelf, plastic-coated, for	fridge compartment
Evaporator cover, white, for	fridge compartment
Product temperature sensor	
SmartCoolingHub	
Roller bars	
Additional lock barrels (up to 10)	

Gross / net capacity	254 / 240 litre
Gross / net capacity	107 / 105 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 2003
Interior dimensions in mm (w / d / h)	440 / 441 / 1105
Interior dimensions in mm (w / d / h)	433 / 433 / 597
Energy consumption in 365 days ¹	657 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	52 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.5 A
Cooling system	forced-air / static
Defrost	automatic / manual
Temperature range	+3 °C to +16 °C / -9 °C to -30 °C
Gradient ²	5.2 °C / 7.9 °C
Max. fluctuation ³	5.7 °C / 5.5 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	4
Shelf material	wire shelves plastic-coated / glass
Usable shelf area in mm (w / d)	440 / 409
Shelf loading	45 kg / 24 kg
Drawers	3
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	89 / 83 kg
Accessories	
Shelf, plastic-coated, for	7113333
Evaporator cover, white, for	9590391
Product temperature sensor	9590407
SmartCoolingHub	6125784
Roller bars	9592756
Additional lock barrels (up to 10)	on request

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

The advantages at a glance

+2 °C SafetyDevice

If the temperature falls below +2 °C due to a malfunction, the SafetyDevice takes control, stabilising the temperature, activating the alarm and protecting the contents from freezing.



Power failure info

The power failure info function reports when the appliance was temporarily without power and what the maximum temperature was during this time. This allows you to better assess the potential loss of quality.

Min./max. temperature log


The min./max. temperature log stores the minimum and maximum interior temperatures and shows on the display whether the storage temperatures were within the tolerance limits.

Easy-to-clean interior

The inner liner made of fully recyclable, robust and odourless polystyrene is manufactured in one piece without joints. This makes it quick and easy to clean the large, rounded corners.

Feedthrough for external sensors

An integrated opening allows a separate sensor to be connected for additional temperature monitoring without having to drill holes or break the door seal.



SRFfg 4001 Performance



Mechanical lock

Liebherr professional appliances are equipped with a mechanical lock and two keys. This ensures that unauthorised persons cannot access your valuable and sensitive stored goods.

SmartMonitoring

The cloud-based digital solution continuously monitors and documents temperatures and alerts you immediately via email, text message or phone if any deviations occur.

Retrofittable WiFi/LAN interface

The retrofittable WiFi/LAN interface enables you to easily connect your appliances with Liebherr SmartMonitoring or existing local systems.

Antimicrobial handle with opening mechanism

The smooth-turning handle contains special antimicrobial substances that make it particularly hygienic. Regular and time-consuming disinfection is not necessary.



Replaceable door seal

Save time and money: the insertable Liebherr door seals are easy to change. If a seal is damaged, you can replace it yourself without any tools. Contact Liebherr Customer Service to purchase replacements.

Self-closing door < 90°

To make loading, unloading and cleaning easier, the appliance door stays open if opened by more than 90°. If the opening angle is less than 90°, it closes automatically for safety.

Quality right down to the smallest detail

Robust glass shelves

For more convenience in the lab, the robust glass shelves of the refrigerators and freezers with spark-proof interior are easy to clean and simple to remove when the door is opened by around 90°.



Explosion protection: ATEX 95

The ATEX-95 certification confirms that the Liebherr spark-free laboratory refrigerators and freezers are suitable for storing explosive and highly flammable materials as defined by EU Directive 2014/34/EU (ATEX).



Super-efficient

Rising electricity prices are increasing the demands on the efficiency of refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of every component. The result is impressive – especially in terms of total operating costs.



±3 °C temperature stability

Temperature fluctuations must be minimal to ensure that the quality of sensitive substances is preserved. Liebherr Laboratory refrigerators have an impressive maximum deviation of just ±3 °C from the set temperature. This not only maintains the storage climate, but also the value of your stored goods.



IEC 61010-2-011 standard

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always safe.



SRFfg 5501

Performance



Gross / net capacity	558 / 441 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	600 / 537 / 1460
Energy consumption in 365 days ¹	399 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	408 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.7 °C / 3.0 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	5
Shelf material	glass
Usable shelf area in mm (w / d)	600 / 537
Shelf loading / device	40 kg / 300 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	92 / 80 kg
Accessories	
Glass shelf	9291929
Perforated metal shelf	
Scanner rail	7435210
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



SRFfg 4001

Performance



Gross / net capacity	394 / 298 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 422 / 1660
Energy consumption in 365 days ¹	421 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	454 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	5.1 °C / 3.2 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	5
Shelf material	glass
Usable shelf area in mm (w / d)	460 / 422
Shelf loading / device	40 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	74 / 68 kg
Accessories	
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



SRFfg 3501

Performance



Gross / net capacity	344 / 261 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1684
Interior dimensions in mm (w / d / h)	460 / 537 / 1460
Energy consumption in 365 days ¹	406 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	388 kJ/h
Refrigerant	R 600a
Sound power level	48 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+3 °C to +16 °C
Gradient ² / max. fluctuation ³	3.6 °C / 3.1 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	4
Shelf material	glass
Usable shelf area in mm (w / d)	460 / 537
Shelf loading / device	40 kg / 180 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
ATEX conformity	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	70 / 60 kg
Accessories	
Glass shelf	9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

Quality right down to the smallest detail

Liebherr offers refrigerators and freezers with a spark-free interior specifically for storing explosive and highly flammable substances in laboratories and in the chemical industry. The inner liners meet the safety requirements of EU Directive 2014/34/EU (ATEX) and have been tested according to the EN 1127-1, IEC 60079-0 and IEC 60079-15 standards by electro-suisse – SEV (Swiss association for electrical and power engineering and information technology), an approved ATEX conformity evaluation organisation.



Easy-to-clean interior

The plastic inner liner is made of polystyrene: a fully recyclable, robust, and odourless plastic. Manufactured seamlessly from one piece, it has no hidden dirt traps, and the large, rounded corners can be cleaned quickly and easily. It's the perfect combination of sustainability and hygiene.



SmartFrost

Where there's no ice, there's no need to defrost: SmartFrost greatly reduces the frost build-up in the interior and on stored products. Defrosting is required less often – and when it is necessary, it is made much easier by the smooth, easy-to-clean interior walls. The evaporator is embedded in foam insulation, ensuring high energy efficiency and uniform cooling.



Super-efficient

Rising electricity prices are increasing the demands on the efficiency of refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of every component. The result is impressive – especially in terms of total operating costs.



±5 °C temperature stability

Sensitive substances cannot be subjected to large deviations from the set storage temperature. Liebherr freezers guarantee a temperature fluctuation of no more than ±5 °C, so that the valuable goods you store in them are optimally protected and their quality is preserved.



IEC 61010-2-011 standard

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always safe.



Compliance with the ATEX Directive

Liebherr laboratory appliances conform to EN/IEC 60079-0 / EN-IEC 60079-7 and comply with EU Directive 2014/34/EU ("ATEX Directive"). With an interior classified according to <Ex> II 3 G Ex ec IIC T6 (declared as Zone 22), they are suitable for flammable substances in closed containers that could form explosive atmospheres.

Laboratory freezers with spark-free interior



SFFfg 5501 Performance

Gross / net capacity	499 / 394 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1684
Interior dimensions in mm (w / d / h)	588 / 517 / 1388
Energy consumption in 365 days ¹	516 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	5.4 °C / 3.3 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	4
Shelf material	glass
Usable shelf area in mm (w / d)	588 / 517
Shelf loading / device	40 kg / 300 kg
Handle	Antimicrobial handle with opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	100 / 95 kg
Accessories	
Full-depth drawer	9797881
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269



SFFfg 4001 Performance

Gross / net capacity	316 / 242 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	403 / 402 / 1588
Energy consumption in 365 days ¹	384 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 290
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system	static
Defrost	manual
Temperature range	-9 °C to -30 °C
Gradient ² / max. fluctuation ³	5.2 °C / 2.4 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	monochrome display, touch buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WiFi/LAN (optional)
Adjustable shelves	5
Shelf material	glass
Usable shelf area in mm (w / d)	403 / 402
Shelf loading / device	40 kg / 270 kg
Handle	Antimicrobial handle with opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	82 / 76 kg
Accessories	
Full-depth drawer	9797881
Castors Ø 80 mm	9086926
Castors Ø 100 mm	9080023
Adjustable feet, 90 - 120 mm	9080022
Adjustable feet, 150 - 180 mm	9086924
Additional lock barrels (up to 5)	on request
Side-by-Side set	on request
SmartModule	6145269

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

Laboratory refrigerators and freezers with spark-free interior



LKUexv 1610
MediLine



LGUex 1500
MediLine



LKexv 1800
MediLine

Gross / net capacity	141 / 130 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	315 kWh
Ambient temperature range	+10°C to +35°C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+3°C to +16°C
Gradient² / max. fluctuation³	3.9°C / 4.8°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	3
Shelf material	glass
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	40 kg
Drawers	
Number of baskets	
Compartment height in mm	
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	41 / 38 kg
Accessories	
Glass shelf	9293629
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	139 / 129 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	454 / 450 / 663
Energy consumption in 365 days¹	294 kWh
Ambient temperature range	+10°C to +35°C
Refrigerant	R 600a
Sound power level	45 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	static
Defrost	manual
Temperature range	-9°C to -26°C
Gradient² / max. fluctuation³	6.6°C / 3.3°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	
Shelf material	evaporator plates
Usable shelf area in mm (w / d)	454 / 450
Shelf loading	24 kg
Drawers	3
Number of baskets	1
Compartment height in mm	
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	43 / 42 kg
Accessories	
Glass shelf	9592697
Stacking kit, white	9590521
Roller bars	6125784
SmartCoolingHub	on request
Additional lock barrels (up to 10)	on request

Gross / net capacity	180 / 160 litre
Exterior dimensions in mm (w / d / h)	600 / 600 / 860
Interior dimensions in mm (w / d / h)	513 / 441 / 702
Energy consumption in 365 days¹	328 kWh
Ambient temperature range	+10°C to +30°C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+1°C to +15°C
Gradient² / max. fluctuation³	10.2°C / 7.4°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	Rotary control with digital thermometer
Power failure alarm	
Fault: warning signal	
Volt-free alarm contact	
Connectivity type	
Connectivity solution	
Interface	
Adjustable shelves	3
Shelf material	glass
Usable shelf area in mm (w / d)	513 / 412
Shelf loading	40 kg
Drawers	
Number of baskets	
Compartment height in mm	
Handle	ergonomic slimline handle
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	41 / 38 kg
Accessories	
Glass shelf	9293631
Stacking kit, white	
Roller bars	
SmartCoolingHub	
Additional lock barrels (up to 10)	

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.

Laboratory fridge-freezer combination with spark-free interior



LCexv 4010
MediLine



Gross / net capacity	fridge compartment
Gross / net capacity	freezer compartment
Exterior dimensions in mm (w / d / h)	
Interior dimensions in mm (w / d / h)	fridge compartment
Interior dimensions in mm (w / d / h)	freezer compartment
Energy consumption in 365 days¹	
Ambient temperature range	
Refrigerant	
Sound power level	
Voltage / Connection rating	
Cooling system	fridge / freezer comp.
Defrost	fridge / freezer comp.
Temperature range	fridge / freezer comp.
Gradient²	fridge / freezer comp.
Max. fluctuation³	fridge / freezer comp.
External cabinet finish	
Door material	
Internal liner material	
Type of control	
Power failure alarm	
Fault: warning signal	
Volt-free alarm contact	
Connectivity type	
Connectivity solution	
Interface	
Adjustable shelves	fridge compartment
Shelf material	fridge / freezer comp.
Usable shelf area in mm (w / d)	fridge compartment
Shelf loading	fridge / freezer comp.
Drawers	freezer compartment
Handle	
Type of lock	
Door hinges	
Gross / net weight	
Accessories	
Glass shelf	
Product temperature sensor	
SmartCoolingHub	
Roller bars	
Additional lock barrels (up to 10)	

Gross / net capacity	254 / 240 litre
Gross / net capacity	107 / 105 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 2003
Interior dimensions in mm (w / d / h)	440 / 441 / 1105
Interior dimensions in mm (w / d / h)	433 / 433 / 597
Energy consumption in 365 days¹	657 kWh
Ambient temperature range	+10°C to +35°C
Refrigerant	R 600a
Sound power level	52 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.5 A
Cooling system	forced-air / static
Defrost	automatic / manual
Temperature range	+3°C to +16°C / -9°C to -30°C
Gradient²	4.0°C / 7.9°C
Max. fluctuation³	3.9°C / 5.5°C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	when mains power return
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Adjustable shelves	4
Shelf material	glass / glass
Usable shelf area in mm (w / d)	440 / 409
Shelf loading	40 kg / 24 kg
Drawers	3
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	92 / 85 kg
Accessories	
Glass shelf	9293629
Product temperature sensor	9590145
SmartCoolingHub	6125784
Roller bars	9592756
Additional lock barrels (up to 10)	on request

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.


Laboratory refrigerators and freezers with stainless steel inner liner



Side-by-side set
Using the side-by-side set, two appliances can be placed next to each other. The required gap between the appliances is maintained, and they are neatly connected by the cover strip. This ensures tidy installation and avoids any condensation or water between the appliances.



U-shaped trayslides
Additional U-shaped trayslides can be retrofitted as required to provide extra storage options.



Plastic-coated grid shelf
If you need more storage space or want to separate stored products and have a better overview, Liebherr appliances can be equipped with additional grid shelves. Made of metal with a polypropylene coating, they are identical to the ones that come as standard in the appliances and you benefit from the same corrosion-resistant and durable extra shelving.



Product temperature sensor
A product temperature sensor for logging product temperatures is available as a retrofit kit for the laboratory appliances with electronic controller. The logged product temperatures can either be read by the electronic controller or transferred to an external documentation system via the existing RS 485 interface.



Foot-pedal door opener
The optional foot-pedal opener is useful when you don't have a hand free.



SmartCoolingHub
The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.

Laboratory refrigerators and freezers and laboratory fridge-freezer combination with plastic inner liner



SmartCoolingHub
The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.



Product temperature sensor
A product temperature sensor for logging product temperatures is available as a retrofit kit for the laboratory appliances with electronic controller. The logged product temperatures can either be read by the electronic controller or transferred to an external documentation system via the existing RS 485 interface.



Special locking
To protect the stored products from unwanted access, special locks are available as accessories for the refrigerators and freezers. This way, different locks can be installed on several appliances to so that only the people responsible for a particular appliance have access to it.

Laboratory refrigerators and freezers and laboratory fridge-freezer combination with plastic inner liner



Stacking Kit
The stacking kit can be used to combine two refrigerators or refrigerators and freezers. This way, different temperature zones are available on a small surface area.




Evaporator cover
To better protect temperature-sensitive goods and prevent them from touching the refrigeration system, a protective plate can be retrofitted in the interior. This prevents direct contact with the refrigeration components so that the goods can be safely stored in the intended area.



Roller bars and height-adjustable feet
The sturdy castors to facilitate transport and allow cleaning underneath and behind the appliance. Two roller sets including mounting accessories are supplied. The height-adjustable feet create the necessary clearance for easy cleaning under the appliance. With an individually adjustable height of 90 to 120 mm, they perfectly compensate for any unevenness on the floor.



Plastic-coated grid shelf
If you need more storage space or want to separate stored products and have a better overview, Liebherr appliances can be equipped with additional grid shelves. Made of metal with a polypropylene coating, they are identical to the ones that come as standard in the appliances and you benefit from the same corrosion-resistant and durable extra shelving.



SmartModule
SmartModule connects refrigerators and freezers in a network with Liebherr SmartMonitoring and allows you to use its extensive digital monitoring and documentation functions. In addition, appliances can be integrated into a customer's existing monitoring system via a local API. The small electronic unit with integrated LAN/WiFi is ready to use as soon as it is mounted on the back of the appliance.



Long drawer
Always keep a good overview of your stored products with this sturdy plastic drawer. With its ergonomic handle, the drawer is very easy for you to open, day in, day out.



Glass shelf
Additional shelves made of high-quality safety glass not only increase storage space but also make it easier to see the goods. They are ideal for storing smaller containers or materials. In addition, the shatterproof glass shelves are quick and easy to clean.



Side-by-side set
Using the side-by-side set, two appliances can be placed next to each other. The required gap between the appliances is maintained, and they are neatly connected by the cover strip. This ensures tidy installation and avoids any condensation or water between the appliances.

Laboratory refrigerators and freezers and laboratory fridge-freezer combination with plastic inner liner



Perforated metal shelf

To ensure that even small items are stored stably in the refrigeration appliances, Liebherr has developed shallow perforated metal shelves especially for this purpose. They are made of coated metal and designed for a maximum load of up to 45 kg. The perforation ensures unhindered air circulation throughout the storage space.



Flexible scanner rail

Scanner rails provide a perfect overview of the materials stored in the refrigerator. Thanks to their flexibility, they can be easily attached to the front of the grid shelves. With correspondingly marked paper cards, they make it easy to sort and find stored products.



Base grid

With the sturdy base grid, you can also make the most of the appliance floor. The grid has an abrasion-resistant coating and protects the inner liner from scratches and other damage.

Laboratory refrigerators and freezers and laboratory fridge-freezer combination with spark-free interior



Product temperature sensor

A product temperature sensor for logging product temperatures is available as a retrofit kit for the laboratory appliances with electronic controller. The logged product temperatures can either be read by the electronic controller or transferred to an external documentation system via the existing RS 485 interface.



SmartCoolingHub

The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.



Special locking

To protect the stored products from unwanted access, special locks are available as accessories for the refrigerators and freezers. This way, different locks can be installed on several appliances so that only the people responsible for a particular appliance have access to it.



Glass shelf

Additional shelves made of high-quality safety glass not only increase storage space but also make it easier to see the goods. They are ideal for storing smaller containers or materials. In addition, the shatterproof glass shelves are quick and easy to clean.



Stacking Kit

The stacking kit can be used to combine two refrigerators or refrigerators and freezers. This way, different temperature zones are available on a small surface area.



Roller bars

The sturdy castors within the roller bars to facilitate transport and allow cleaning underneath and behind the appliance. Two roller sets including mounting accessories are supplied.

Laboratory refrigerators and freezers and laboratory fridge-freezer combination with spark-free interior



Height-adjustable feet

The height-adjustable feet create the necessary clearance for easy cleaning under the appliance. With an individually adjustable height of 90 to 120 mm, they perfectly compensate for any unevenness on the floor.




Perforated metal shelf

To ensure that even small items are stored stably in the refrigeration appliances, Liebherr has developed shallow perforated metal shelves especially for this purpose. They are made of coated metal and designed for a maximum load of up to 45 kg. The perforation ensures unhindered air circulation throughout the storage space.



Flexible scanner rail

Scanner rails provide a perfect overview of the materials stored in the refrigerator. Thanks to their flexibility, they can be easily attached to the front of the grid shelves. With correspondingly marked paper cards, they make it easy to sort and find stored products.



SmartModule

SmartModule connects refrigerators and freezers in a network with Liebherr SmartMonitoring and allows you to use its extensive digital monitoring and documentation functions. In addition, appliances can be integrated into a customer's existing monitoring system via a local API. The small electronic unit with integrated LAN/WiFi is ready to use as soon as it is mounted on the back of the appliance.



Long drawer

Always keep a good overview of your stored products with this sturdy plastic drawer. With its ergonomic handle, the drawer is very easy for you to open, day in, day out.



Side-by-side set

Using the side-by-side set, two appliances can be placed next to each other. The required gap between the appliances is maintained, and they are neatly connected by the cover strip. This ensures tidy installation and avoids any condensation or water between the appliances.



Pharmaceutical refrigerators – medical refrigeration solutions with maximum safety

Temperature-sensitive medicines, vaccines and samples must be stored in the most reliable conditions. To be available whenever they are needed, they must be stored round the clock in maximum safety.

Liebherr pharmaceutical refrigerators compliant with DIN 13277 have been specially designed for these particular requirements. With their dynamic cooling system, highly effective insulation and precise temperature control, they guarantee absolutely reliable storage of sensitive substances and preparations. Visual and audible alarm systems provide additional safety.

The combination of maximum temperature stability, energy efficiency, robustness and ease of use lightens your daily workload – and saves you money in the long term because of the extremely low energy and operating costs.

Pharmaceutical refrigerators



MediLine



Perfection series

	MediLine Pharmaceutical storage MKUv	Perfection series Pharmaceutical storage HMFvh
Temperature stability	Refrigerators +/-3 K deviation from setpoint	Refrigerators +/-2 K deviation from setpoint (model version H63 +/-3 K)
	Calibration option	Calibration option
Storage safety	Visual and audible alarms	Visual and audible alarms
	Alarm relay	Alarm relay
	Alarm test function	Alarm test function
	+2 °C SafetyDevice function	+2 °C SafetyDevice function
	Alarm with battery backup (12 h) immediately upon power failure	Alarm with battery backup (12 h) immediately upon power failure
	Alarm history with real-time clock and 6 events	Alarm history with real-time clock and 10 events
	NTC product sensor	PT1000 product sensor
	Min./max. temperature log	Min./max. temperature log
	Fulfils DIN 13277	Fulfils DIN 13277
	Self-closing door at < 90°	Self-closing door at < 90°
	Custom alarm settings possible	Custom alarm settings possible
	Mechanical lock	Electronic lock
Interfaces	RS485 interface	Integrated LAN/WiFi
	Modbus RTU communication protocol	Local API
		USB interface for reading the data logger
SmartMonitoring	SmartCoolingHub can be retrofitted	SmartModule integrated
Features	LED 7-segment display with buttons	2.4" touch & swipe colour display
		Individually adjustable maintenance timer
	Castors/adjustable feet as accessories, 75 cm wide appliances with castors as standard	Castors/adjustable feet as accessories, 75 cm wide appliances with castors as standard
	Evaporator cover (stops items freezing to inner liner)	Evaporator cover (stops items freezing to inner liner)
	Sensor feedthrough	Sensor feedthrough
	Glass door models with ceiling lighting	Insulated and glass door models with vertical lighting
	Ergonomic slimline handle with opening mechanism	Antimicrobial handle with opening mechanism
Energy consumption		Ultra-efficient
Compliance	Safety according to IEC 60335-2-89	Safety according to IEC 61010-2-011

The advantages at a glance

+2 °C SafetyDevice

If the temperature falls below +2 °C due to a malfunction, the SafetyDevice takes control, stabilising the temperature, activating the alarm and protecting the contents from freezing.

Power failure alarm

If a malfunction occurs, an integrated battery provides a visual and audible alarm and takes over the power supply. As soon as the power is restored, the time of failure and the maximum temperature reached are displayed.



Vertical LED lighting

Vertical LED lighting provides optimal illumination of the interior over the entire height of the appliance. This not only saves you time looking for things, but, above all, cuts energy costs.

LightAlarm

In the event of an uncontrolled temperature rise or other problems, the interior light of the appliance starts flashing. This quickly shows when action is needed.

Easy-to-clean interior


The inner liner made of fully recyclable, robust and odourless polystyrene is manufactured in one piece without joints. This makes it quick and easy to clean the large, rounded corners.

Feedthrough for external sensors

An integrated opening allows a separate sensor to be connected for additional temperature monitoring without having to drill holes or break the door seal.

Integrated data logger

The integrated logger records the temperature profile, alarm history and service information for up to five years. The data can be read out directly from the appliance via the USB interface.



HMVh 4011 Perfection



SmartLock

To prevent products from accidentally entering circulation after an interruption in the cold chain, SmartLock automatically locks the door if there is an alarm. Only authorised persons can unlock it again.

SmartMonitoring

The cloud-based digital solution continuously monitors and documents temperatures and alerts you immediately via email, text message or phone if any deviations occur.

Integrated WiFi/LAN interface

The integrated WiFi/LAN interface enables you to easily connect your appliances with Liebherr SmartMonitoring or existing local systems.

Min./max. temperature log

The min./max. temperature log stores the minimum and maximum interior temperatures and shows on the display whether the storage temperatures were within the tolerance limits.

Antimicrobial handle with opening mechanism

The smooth-turning handle contains special antimicrobial substances that make it particularly hygienic. Regular and time-consuming disinfection is not necessary.



Replaceable door seal

Save time and money: the insertable Liebherr door seals are easy to change. If a seal is damaged, you can replace it yourself without any tools. Contact Liebherr Customer Service to purchase replacements.

Self-closing door < 90°

To make loading, unloading and cleaning easier, the appliance door stays open if opened by more than 90°. If the opening angle is less than 90°, it closes automatically for safety.

Quality right down to the smallest detail



Pharmacy drawers

Optimal overview, easy access, high temperature stability: the practical organisational system made of cold-conducting aluminium comes with a transparent front, perforated base, flexible dividing walls and a ¾-extension drawer. Medicines, vaccines and other items can be quickly found – and the door closed again with minimal loss of cold air.



Electronic lock with remote control

Liebherr appliances can be securely locked with a PIN code. Locking and unlocking via remote control is also possible. This allows any number of users to lock and unlock one or more appliances without having to share a key.



Grid shelf with pull-out stop

Stable, durable, allows air to circulate: the robust, corrosion-free wire shelves made from coated steel support even heavy goods. At the same time, they guarantee constant air circulation for temperature stability. A pull-out stop prevents the shelf from sliding out when removing items.



Ultra-efficient

Rising electricity prices are increasing the demands on the efficiency of refrigerators and freezers. From the compressor to the seal, to the lighting and electronics, Liebherr fully utilises the savings potential of every component. The result is impressive – especially in terms of total cost of ownership.



±2 °C temperature stability

Temperature fluctuations must be minimal to ensure that the quality of sensitive substances is preserved. Liebherr Pharmaceutical refrigerators have an impressive maximum deviation of just ±2 °C from the set temperature. This not only maintains the storage climate, but also the value of your stored goods. (Model version H63 with temperature stability +/-3 K).



DIN 13277 compliance

Laboratory and pharmacy refrigerators from Liebherr meet all the necessary equipment and performance criteria to fully comply with DIN 13277. DIN 13277 defines the requirements and test specifications for refrigerators and freezers used in laboratories and for storing medicinal products.



IEC 61010-2-011 standard

Liebherr refrigerators and freezers specially developed for storing temperature-sensitive products are CE safety-compliant. This ensures that all mechanical and electrical requirements for injury-free operation are met – and that you and your team are always safe.



HMFvh 5511
Perfection



HMFvh 5501
Perfection



Gross / net capacity	588 / 435 litre
Exterior dimensions in mm (w / d / h)	747 / 769 / 1793
Interior dimensions in mm (w / d / h)	600 / 536 / 1460
Energy consumption in 365 days ¹	360 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	475 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+5 °C
Gradient ² / max. fluctuation ³	3.3 °C / 2.0 °C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	Vertical LED light strip recessed in left wall with separate switch
Number of shelves / Adjustable shelves	6 / 5
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	600 / 536
Shelf loading / device	60 kg / 300 kg
Castors	castors with brake at the front, fixed castors at the rear
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	electronic, with remote control / right, reversible on site
Gross / net weight	111 / 102 kg
Accessories	
Shelf, plastic-coated	7113310
Base grid / Glass shelf	7113314 / 9291929
Scanner rail	7435210
Castors Ø 80 mm	9086926
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Side-by-Side set	on request
Additional remote controls	6123395
Digital input for electronic lock	9086958

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



HMFvh 4011
Perfection



HMFvh 4001
Perfection



Gross / net capacity	420 / 297 litre
Exterior dimensions in mm (w / d / h)	597 / 654 / 1884
Interior dimensions in mm (w / d / h)	460 / 423 / 1660
Energy consumption in 365 days ¹	389 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	463 kJ/h
Refrigerant	R 600a
Sound power level	49 dB(A)
Voltage / Connection rating	220 - 240V~ / 2.0 A
Cooling system / Defrost	forced-air / automatic
Temperature range	+5 °C
Gradient ² / max. fluctuation ³	3.0 °C / 2.4 °C
External cabinet finish	steel / white
Door material	glass
Internal liner material	commercial grade moulded polystyrol
Type of control	2.4" touch & swipe colour display
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type / Connectivity solution	SmartModule / Integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	Vertical LED light strip recessed in left wall with separate switch
Number of shelves / Adjustable shelves	6 / 5
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	460 / 423
Shelf loading / device	45 kg / 225 kg
Handle	Antimicrobial handle with opening mechanism
Access ports	1 x Ø 10 mm
DIN 13277	yes
Type of lock / Door hinges	electronic, with remote control / right, reversible on site
Gross / net weight	89 / 83 kg
Accessories	
Shelf, plastic-coated	7113308
Base grid / Glass shelf	7113312 / 9293493
Perforated metal shelf	9029022
Scanner rail	7435208
Castors Ø 80 mm / Ø 100 mm	
Adjustable feet, 90 - 120 mm / 150 - 180 mm	9080022 / 9086924
Side-by-Side set	on request
Additional remote controls	6123395
Digital input for electronic lock	9086958

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



Vertical LED lighting

Vertical LED lighting provides optimal illumination of the interior over the entire height of the appliance. Thanks to the perfect overview on all levels, the required substance is immediately at hand, the door can be quickly closed again, and the interior temperature remains stable. This saves you time looking for things – and above all energy costs.



Pharmacy drawers

Optimal overview, easy access, high temperature stability: the practical organisational system made of cold-conducting aluminium comes with a transparent front, perforated base, flexible dividing walls and a ¾-extension drawer. Medicines, vaccines and other items can be quickly found – and the door closed again with minimal loss of cold air.

Pharmaceutical refrigerators compliant with DIN 13277 with organisational system



HMfVh 5511
ver. H63 Perfection



HMfVh 5501
ver. H63 Perfection



HMfVh 4011
ver. H63 Perfection



HMfVh 4001
ver. H63 Perfection



Gross / net capacity	
Exterior dimensions in mm (w / d / h)	
Interior dimensions in mm (w / d / h)	
Energy consumption in 365 days¹	
Ambient temperature range	
Refrigerant	
Sound power level	
Voltage / Connection rating	
Cooling system / Defrost	
Temperature range	
Gradient² / max. fluctuation³	
External cabinet finish	
Door material	
Internal liner material	
Type of control	
Power failure alarm	
Fault: warning signal	
Volt-free alarm contact	
Connectivity type / Connectivity solution	
Interface / Data logger	
Interior light	
Number of shelves / Adjustable shelves	
Number of drawers	
Shelf material	
Usable shelf area in mm (w / d)	
Shelf loading / device	
Castors	
Handle	
Type of lock	
Door hinges	
Gross / net weight	
Accessories	
Shelf, plastic-coated	
Base grid / Glass shelf	
Perforated metal shelf / Scanner rail	
Castors Ø 80 mm / Ø 100 mm	
Adjustable feet, 90 – 120 mm / 150 – 180 mm	
Side-by-Side set	
Additional remote controls	
Digital input for electronic lock	

588 / 355 litre
747 / 769 / 1793
556 / 460 / 1460
400 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
3.1 °C / 2.6 °C
steel / white
glass
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
Vertical LED light strip recessed in left wall with separate switch
1 / 1
7
wire shelves plastic-coated
556 / 460
50 kg / 300 kg
castors with brake at the front, fixed castors at the rear
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
101 / 97 kg
7113310
7113314 / 9291929
- / 7435210
9086926 / -
9080022 / 9086924
on request
6123395
9086958

558 / 355 litre
747 / 769 / 1793
556 / 460 / 1460
171 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
2.8 °C / 2.3 °C
steel / white
steel
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
LED lighting column, left
1 / 1
7
wire shelves plastic-coated
556 / 460
50 kg / 300 kg
castors with brake at the front, fixed castors at the rear
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
106 / 100 kg
7113310
7113314 / 9291929
- / 7435210
9086926 / -
9080022 / 9086924
on request
6123395
9086958

420 / 235 litre
597 / 654 / 1884
406 / 370 / 1660
409 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
4.1 °C / 2.2 °C
steel / white
glass
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
Vertical LED light strip recessed in left wall with separate switch
1 / 1
8
wire shelves plastic-coated
406 / 370
50 kg / 225 kg
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
82 / 69 kg
7113308
7113312 / 9293493
9029022 / 7435208
9080022 / 9086924
on request
6123395
9086958

394 / 235 litre
597 / 654 / 1884
406 / 370 / 1660
172 kWh
+10 °C to +35 °C
R 600a
49 dB(A)
220 – 240V~ / 2.0 A
forced-air / automatic
+5 °C
4.9 °C / 2.6 °C
steel / white
steel
commercial grade moulded polystyrol
2.4" touch & swipe colour display
immediately upon power failure for at least 12 hrs
visual and audible
yes
SmartModule / Integrated, removable
WiFi/LAN / integrated, USB interface
LED lighting column, left
1 / 1
8
wire shelves plastic-coated
406 / 370
50 kg / 225 kg
Antimicrobial handle with opening mechanism electronic, with remote control
right, reversible on site
69 / 64.5 kg
7113308
7113312 / 9293493
9029022 / 7435208
9086926 / 9080023
9080022 / 9086924
on request
6123395
9086958

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



MKUv 1613
MediLine



MKUv 1610
MediLine



Gross / net capacity	152 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	408 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	5.1 °C / 4.9 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Number of shelves	4
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	48 / 45 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	142 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	273 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	4.3 °C / 4.6 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Number of shelves	4
Adjustable shelves	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	42 / 39 kg
Accessories	
Shelf, plastic-coated	7113333
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

¹ Measured at +25°C ambient temperature and +5°C set temperature for fridges and -20°C for freezers.



MKUv 1613 ver. H63
MediLine



MKUv 1610 ver. H63
MediLine



Gross / net capacity	152 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	369 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	4.1 °C / 1.5 °C
External cabinet finish	steel / white
Door material	glass door
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	LED ceiling light strip with separate switch
Number of shelves	1
Number of drawers	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	51 / 48 kg
Accessories	
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

Gross / net capacity	142 / 109 litre
Exterior dimensions in mm (w / d / h)	601 / 618 / 820
Interior dimensions in mm (w / d / h)	440 / 435 / 670
Energy consumption in 365 days¹	273 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Sound power level	47 dB(A)
Voltage / Connection rating	220 - 240V~ / 1.0 A
Cooling system	forced-air
Defrost	automatic
Temperature range	+5 °C
Gradient² / max. fluctuation³	2.8 °C / 1.3 °C
External cabinet finish	steel / white
Door material	steel
Internal liner material	commercial grade moulded polystyrol
Type of control	LED 7-segment display with buttons
Power failure alarm	immediately upon power failure for at least 12 hrs
Fault: warning signal	visual and audible
Volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	Retrofittable
Interface	RS485
Interior light	
Number of shelves	1
Number of drawers	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	45 kg
Handle	slimline handle with integrated opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross / net weight	45 / 42 kg
Accessories	
Stacking kit, white	9592697
Roller bars	9590521
SmartCoolingHub	6125784
Additional lock barrels (up to 10)	on request

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
³ Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

Pharmaceutical refrigerators compliant with DIN 13277



Glass shelf
Additional shelves made of high-quality safety glass not only increase storage space but also make it easier to see the goods. They are ideal for storing smaller containers or materials. In addition, the shatterproof glass shelves are quick and easy to clean.



Plastic-coated grid shelf
If you need more storage space or want to separate stored products and have a better overview, Liebherr appliances can be equipped with additional grid shelves. Made of metal with a polypropylene coating, they are identical to the ones that come as standard in the appliances and you benefit from the same corrosion-resistant and durable extra shelving.



Base grid
With the sturdy base grid, you can also make the most of the appliance floor. The grid has an abrasion-resistant coating and protects the inner liner from scratches and other damage.



Height-adjustable feet
The height-adjustable feet create the necessary clearance for easy cleaning under the appliance. With an individually adjustable height of 90 to 120 mm, they perfectly compensate for any unevenness on the floor.



Roller bars
The sturdy castors within the roller bars have a diameter of 25 mm (total height 30 mm) to facilitate transport and allow cleaning underneath and behind the appliance. Two roller sets including mounting accessories are supplied.



Special locking
To protect the stored products from unwanted access, up to 10 additional special locks are available as accessories for the refrigerators and freezers. This way, different locks can be installed on several appliances so that only the people responsible for a particular appliance have access to it.



Remote control electronic door lock
With additional remote controls for refrigerators and freezers with electronic door locks, you can allow other people to access stored goods while retaining full control at all times. For example, you can individually control whether renewed access should be granted or denied to a person by activating or deactivating their remote control.



Stacking kit
The stacking kit can be used to combine two refrigerators or refrigerators and freezers. This way, different temperature zones are available on a small surface area.



Digital input for electronic lock
The digital input for the electronic lock allows Liebherr appliances to be integrated into existing external time and attendance or access control systems. When a voltage signal triggers the remote box, the electronic lock opens and allows access to the appliance. Possible applications include connection to access control systems or integration into goods management applications.

Pharmaceutical refrigerators compliant with DIN 13277



SmartCoolingHub
The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.



Perforated metal shelf
To ensure that even small items are stored stably in the refrigeration appliances, Liebherr has developed shallow perforated metal shelves especially for this purpose. They are made of coated metal and designed for a maximum load of up to 45 kg. The perforation ensures unhindered air circulation throughout the storage space.



Flexible scanner rail
Scanner rails provide a perfect overview of the materials stored in the refrigerator. Thanks to their flexibility, they can be easily attached to the front of the grid shelves. With correspondingly marked paper cards, they make it easy to sort and find stored products.



Castors
The sturdy castors facilitate transport and allow quick cleaning underneath and behind the appliance. A total of four castors including mounting accessories are supplied. Two of the castors also have a locking brake.



Side-by-Side set
Using the side-by-side set, two appliances can be placed next to each other. The required gap between the appliances is maintained, and they are neatly connected by the cover strip. This ensures tidy installation and avoids any condensation or water between the appliances.



SmartMonitoring saves you work and worry


In medicine and research, precision and safety are of the utmost priority – and it also applies to storing sensitive substances. Laboratory samples, vaccines and medicines that have to be refrigerated require constant conditions with precisely defined temperature ranges. The strict specifications and DIN standards on the storage of medicines place great demands on staff.

SmartMonitoring significantly relieves the workload for these time-consuming and laborious duties. The digital monitoring solution automatically and continuously monitors and fully documents all the relevant appliance data for you and alerts you immediately if any deviations occur. And you can concentrate on what matters most: your research, your customers or your patients.

Availability varies by country, please contact your Liebherr Account Manager for details.

Maximum safety, always in view

The combination of a reliable Liebherr appliance and digital SmartMonitoring guarantees optimal protection for sensitive substances. The cloud-based solution monitors and documents temperature stability round the clock and alerts you immediately if deviations occur. Preventing problems before they arise is the definition of maximum safety.



Continuous monitoring of precise, constant temperature

SmartMonitoring constantly checks the storage temperature, even for multiple appliances at different locations. The digital monitoring solution thus ensures precise temperature stability at all times – and safeguards the quality of your stored medicines, vaccines, samples and tissue.



Everything at a glance on the SmartMonitoring dashboard

You can view all measurements and temperature data, alarm notifications and appliance status at any time on the web-based, intuitively operated SmartMonitoring dashboard, even for multiple appliances at different locations. With maximum safety always in view, you can relax and concentrate fully on your work.



Complete documentation without manual paperwork

SmartMonitoring constantly documents the temperature and all other refrigeration parameters for your stored substances. The automatically generated reports are saved for 6 months and can be viewed and downloaded at any time. This lightens the daily workload and helps you demonstrate compliance.

Cloud alarm for double protection

If the appliance is accidentally switched off or disconnected from the power supply, a message is triggered by the cloud alarm. You can also use SmartMonitoring to define an additional, even tighter temperature limit to trigger the alarm.



The availability of SmartMonitoring varies by country.

Find out more about SmartMonitoring here: home.liebherr.com/smartmonitoring



Immediate alarms in the event of deviations

If there are deviations in the storage temperature, you can be immediately alerted by email, text message or phone. This way, you can react before problems arise. If an incident occurs, the alarm list will show the minimum and maximum values so you can assess any potential damage.

Maximum safety and convenience with SmartMonitoring

Enjoy the advantages of Liebherr's digital monitoring solution:

- **Optimal protection of your valuable products** by monitoring a constant, precise storage temperature
- **Fully documented proof** of temperature compliance
- **Prevention of damage and loss of quality** thanks to reliable alarm systems
- **More time for you to focus on your work** by eliminating time-consuming checks and documentation

“SmartMonitoring takes care of refrigeration for us. It’s one less thing to worry about.”



The outpatient centre of Söflingen day clinic treats around 30 patients every day in three operating theatres, which includes providing medication. To ensure their effectiveness, reliable cooling of the medicines must be guaranteed at all times. SmartMonitoring takes over this time-consuming and stressful task at the clinic.

The pharmaceutical fridge combined with SmartMonitoring from Liebherr lightened the workload as soon as it was installed.

Complex and time-consuming tasks that SmartMonitoring performs at Söflingen day clinic:

1. Monitoring the precisely set temperature
2. Sending alarms via email, text message or phone if temperature fluctuations occur
3. Documenting storage conditions and clearly presenting all the relevant data on the SmartMonitoring dashboard
4. Ensuring that the stored medicines are refrigerated at a constant, precise temperature and are always available for use



Watch the case study video for more information

Dr. Jana Wichmann, manager of the Söflingen day clinic

“When the fridge arrived, a team came along to set everything up. And it all works perfectly!”

“We love SmartMonitoring because it lets us concentrate on what really matters: emergency medicine.”



The German Red Cross has nine ambulance stations in Ulm and Heidenheim, with 400 employees and 50 vehicles. The medicines have to be kept refrigerated with maximum safety to be constantly available for use in an emergency. This is ensured by reliable pharmaceutical refrigerators as well as SmartMonitoring from Liebherr, which guarantees maximum storage safety at all the sites.

SmartMonitoring is in use day and night for safe storage and to lighten the workload at the ambulance station in Ulm:

1. Continuously monitoring temperature stability
2. Sending alarms via email, text message or phone if deviations occur
3. Automatically documenting and generating reports on all relevant data
4. User-friendly presentation of the data on the dashboard



Watch the case study video for more information


Lars Grau, Head of Materials management and Medical devices

“SmartMonitoring makes it possible to incorporate several ambulance stations in the system and monitor them all from one place.”

SmartMonitoring – it's that easy to be on the safe side.

There are various ways to enjoy all the benefits of our digital monitoring solution. What they all have in common is that they are simple and convenient. Liebherr will be happy to help you take your first steps towards maximum safety. Lightening your workload right from the very start.

Network-capable medical or laboratory appliance



The new generation of research, laboratory and medical appliances are either already equipped with the SmartModule or can be retrofitted with it and connected via LAN or WiFi to SmartMonitoring. Predecessor models can be connected via the SmartCoolingHub (with up to 20 appliances).

Data processing

The data collected from the SmartModule and SmartCoolingHub is then processed in the cloud or via a local interface.

Visualisation

Always have the data from your appliances in view with the SmartMonitoring dashboard or your own monitoring solution.



Get your licence to chill

With the right licence, you can take full advantage of the professional SmartMonitoring solutions from Liebherr. This includes all the basic functions such as monitoring, documentation and email alerts.

- 36 month term from activation
- Budget friendly – we won't auto renew your subscription
- One licence for each monitored appliance (refrigerator/freezer)
- Authorisation for any number of users
- User and appliance management (role-based)
- Additional alerts via text message and phone optionally available

If your appliance is fitted with SmartModule, register now and get a free 6-month trial licence.



SmartCoolingHub (including 3 year basic licence)

The SmartCoolingHub provides the basis for connecting your professional Liebherr appliances. Up to 20 network-capable Liebherr appliances can be connected via cable.




RS485 connection cable

The ModBUS-compatible 5-metre cable connects your appliance to the SmartCoolingHub. If you want to connect several appliances, you need an additional cable for each appliance.



RS485 connector plug

To link up to the SmartCoolingHub, as well as the connection cable you need the RS485 connector plug. If several appliances are connected, you need an additional plug for each appliance.



SmartModule

SmartModule connects Liebherr appliances of the Performance series to SmartMonitoring or existing monitoring systems. The small unit with integrated LAN/WiFi is ready to use as soon as it is mounted on the back of the appliance.



Local interface

Liebherr appliances can also be used with existing monitoring solutions. The SmartModule acts as a local interface for transferring measurement data to your existing monitoring system.

You can find out if your appliance can be connected at: home.liebherr.com/smartmonitoring

If you already have your own monitoring solution, you can integrate your Liebherr appliances via a local API interface.



Our catalogue programme

Liebherr commercial appliances can be found at specialist retailers where providing first-class service and expert advice are their top priorities.

You can find an overview of other Liebherr appliances in our catalogues. Available in stores or at home.liebherr.com.



BIM data now available

The cooperation between Liebherr-Hausgeräte and Specifi® gives planners and dealers worldwide access to a digital Liebherr appliances library with BIM models for the food service and scientific industries. Compatible with AutoCAD® and Revit.

home.liebherr.com/bimdata



For more information about our technical specifications, go to: home.liebherr.com/scientifichealthcare

Subject to technical changes, errors and different images and text. Colours may differ due to media used.
For the latest available data go to home.liebherr.com.
Printed in Germany by Raiff & Wurzel Druck GmbH. 7900 778-04/01.2023



Scientific and Healthcare 2023
home.liebherr.com

