

FLW2506 Powerful model in tower version

The FL models shown here have higher cooling capacity, powerful circulating pumps, and internal bath volumes of up to 30 liters. 2 variants: Air-cooled (FL) and water-cooled (FLW).

Optional heating function


On request, we also offer our FL recirculating chillers with an additional integrated heating function and other special solutions. Our product experts will be happy to advise you individually in order to design a temperature control unit that is exactly right for your needs. Just give us a call!



Product features

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Reliable Microprocessor PID temperature control
- Precise PID temperature control
- Powerful immersion pumps, suitable for continuous operation
- Permissible temperature in return line +80°C
- Easy filling from the top with hinged protective lid
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)
- Pressure Indicator

Pump capacity



Medium: Water

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

Pump capacity flow rate l/min	60
Pump capacity flow pressure bar	0.5 ... 6
Power consumption A	15

Order No. 9676025.03

Cooling capacity (Ethanol)

°C	20	10	0	-10
kW ¹	2.5	1.9	1	0.3

Refrigerant stage 1

Refrigerant	R452A
Filling weight g	940
Global Warming Potential for R452A	2140
Carbon dioxide equivalent t	2.0116

¹ Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 °C measured with ethanol; over 20 °C with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 °C. Performance values may differ with other bath fluids.

Technical data

Available voltage versions

Order No. 9 676 025

Available voltage versions:

9676025.13	230V/60Hz (Nema N6-20 Plug) (R404A)
9676025.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F) (R452A)

Cooling

Cooling of compressor 1-stage Water

Cooling water pressure max. bar 6

Recommended cooling water properties

Cooling water temperature range °C 20

Cooling water difference pressure bar 2

Cooling water consumption l/min 4.1

Bath

Bath tank Stainless steel

Other

Sound pressure level dbA 61

Classification Classification I (NFL)

IP Code IP 21

Pump type Immersion Pump

Electronics

Interfaces Alarm output, RS232, Stakei

Temperature control PID1

Temperature display LED

Temperature setting Keypad

Dimensions and volumes

Weight kg 160

Cooling Water Connection in G $\frac{3}{4}$

Barbed fittings inner diameter mm 1"

Dimensions cm (W × L × H) 60 x 76 x 115

Filling volume l 24 ... 30

Pump connections G1 $\frac{1}{4}$ " male

Temperature values

Setting the resolution of the temperature display °C 0.1

Return flow temperature max. °C	80
Working temperature range °C	-15 ... +40
Temperature stability °C	±0.5
Ambient temperature °C	+5 ... +40
Setting the resolution of the temperature display °C	0.1

All Benefits



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Precise
PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C



Connection of additional equipment
Stakei connections for solenoid valve