

## DYNEO DD-1201F Refrigerated / heating circulator

Refrigerated circulators of the DYNEO series distinguish themselves with a great price-performance ratio. The instruments offer high heating/cooling capacities for short heat-up and cool-down times. The refrigerated circulators work precisely and reliably even at higher ambient temperatures up to +40 °C. Either in basic research, in material testing or in technical systems – the DYNEO refrigerated circulators offer functional solutions for every requirement and budget.

The DYNEO DD-1201F refrigerated circulator is exceptionally versatile with a bath opening of 35 x 41 cm (width x depth) and a bath depth of 30 cm. The resulting bath volume of 50 liters makes it possible to control the temperature of large objects, or many smaller objects, directly in the bath.

This cooling machine uses natural, environmentally-friendly refrigerant and was developed with a focus on energy efficiency. This means significant savings of up to 70% with respect to the operating costs for numerous applications, which also means faster amortization of the procurement cost. At the same time, the lower energy consumption positively contributes to climate protection.



### Optional analog and digital interface

DYNEO circulators can optionally be equipped with analogue or digital interfaces. To request the options, order number must be extended with .d for the digital and .a for the analog interface (9XXX XXXX.A / 9XXX XXX.D)



### Product features

- Optimized cooling coil design saves space in the bath tank
- powerful and infinitely adjustable pressure pump
- Flow rate 27 l/min, pressure 0.7 bar
- easy switching between internal and external circulation
- large color TFT display, multilingual interface
- central rotary knob (controller) simplifies operation
- Integrated programmer
- Integrated external Pt100 connection
- USB connection
- RS232 interface or analog interfaces (optional)
- integrated drain makes emptying liquid easy and safe.
- Bath cover included with delivery
- removable ventilation grid
- Powerful cooling machines
- For internal and external applications
- Integrated pump connection M16×1
- For internal and external applications

## Technical data

Available voltage versions		Cooling	
Order No.	9 021 718	Cooling of compressor	1-stage Air
Available voltage versions:			
9021718.N1.04	230V/50-60Hz (UK Plug Type BS1363A) (R1270)		
9021718.N1.05	200-230V/50-60Hz (CH Plug Type SEV 1011) (R1270)		
9021718.N1.33	200-230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F) (R1270)		
9021718.N1.33.chn	200-230V/50-60Hz (CN Plug) (R1270)		
9021718.N1.22	100-115V/50-60Hz (Nema N5-20 Plug) (R1270)		
Bath		Other	
Bath tank	Stainless steel	Classification	Classification III (FL)
Bath cover	integrated	Pump function	Pressure Pump
Usable bath opening cm (W x L / D)	35 x 40 / 30	Pump type	Immersion Pump
		User Interface Language	Chinese, English, French, German, Italian, Japanese, Korean, Portuguese, Russian, Spanish
Electronics		Dimensions and volumes	
Interfaces	Alarm output optional, REG/EPROG optional, RS232 optional, Standby-Input optional, USB	Weight kg	68
External pt100 sensor connection	integrated	Barbed fittings inner diameter mm	8/12 mm
Integrated programmer	8x60 steps	Dimensions cm (W x L x H)	45 x 64 x 95
Temperature control	PID3	Filling volume l	48 ... 56
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	3.5" TFT Display		
Temperature setting	Shaft Encoder		
Electronic Timer h:min	00:00 ... 99:59		
Temperature values		Included in delivery	
Setting the resolution of the temperature display °C	0.01	2 Barbed fittings for tubing 8 and 12 mm ID. (Pump connections M16x1 male)	
Working temperature range °C	-40 ... +100		
Temperature stability °C	±0.01		
Ambient temperature °C	+5 ... +40		
Temperature display resolution °C	0.01		

## All Benefits



**Handle with ease.**  
Makes day-to-day work easy. Comfortably move your JULABO Circulator around by using the ergonomic handles (front and rear).



**Highly precise**  
PID Temperature control with drift compensation and adjustable control parameters, temperature stability  $\pm 0.01 \dots \pm 0.02 \text{ } ^\circ\text{C}$



**Wide range.**  
Refrigerated and heating circulator in various combinations, circulator in various sizes. Maximum flexibility through a large selection of accessories.



**Brilliance. In color.**  
Large color display with vivid luminance is easy to read, even from a large distance.



**Information. Everything clear.**  
Information in plain text on a large color screen.



**Multi-lingual.**  
Operation in multiple languages.



**Turn. Push. Go.**  
Easy operation of all parameters using the central controller.



**Programmer. Integrated.**  
The integrated internal programmer makes it possible to automatically run temperature time profiles.



**Powerful. Adjustable.**  
Strong pressure pump, continuously adjustable.



**USB.**  
Remote control made easy using the integrated USB interface.



**RS232.**  
Connection using the optional RS232 interface.



**Analog I/O.**  
Analog interfaces for integration into process control systems (optional).



**Temperature. Under control.**  
External Pt100 sensor connection for precise measurement and control directly in the external application.



**Fill level. Monitored.**  
Fill level indicator on the display for heat-transfer liquid.



**Process stability.**  
Early warning - visual and acoustic - of critical states increases process stability.



**Process. Under control.**  
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



**ATC3. Calibration.**  
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



**Stable. Mobile.**  
Rubber feet keep JULABO Circulators standing firm. Larger and more powerful units also have integrated rollers for easy handling.



**Connection. Easy.**  
Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



**100 % Cooling capacity**  
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures