

Model: SUPREME plus M

Reference no.: 79-200660-021

Correct use: pressurised gas cylinders - inside storage



Product group:	safety storage cabinet
Fire resistance (FR):	Type G90
Catalogue page:	276
Doors can be opened with minimum effort, design:	wing door
Door technology:	classical
Door hinge:	right
Access control with cylinder lock:	✓
Enhanced ventilation concept - ventilation in every cabinet level:	✓
Outer width [mm]:	595 - (23.43 inch)
Outer depth [mm]:	610 - (24.02 inch)
Outer height [mm]:	2070 - (81.50 inch)

Adjustable feet for level equalisation:	✓
Material outer carcass:	sheet steel, powder-coated
Gross weight [kg]:	350 - (771.62 lbs)
Inner width [mm]:	430 - (16.93 inch)
Inner depth [mm]:	388 - (15.28 inch)
Inner height [mm]:	1826 - (71.89 inch)
Material inner carcass:	decor panels
Earthing connection according to TRGS 727 available:	1
Number of earthing connections:	2
Exhaust air connection included:	NW 75/110
Standing surface material:	sheet steel, powder-coated
Marked drilling areas for gas pipes and electrical cables.	✓
Number of horizontal installation rails for mounting gas fittings:	2
Number of cylinder holders:	1
Number of retaining belts:	2
Connection for purging gas pipe:	✓
Includes robust roll-in flap:	✓
Mark of approval by TÜV:	GS mark
Type-tested by recognised test institutes according to:	DIN EN 14470-2
TÜV-tested according to:	DIN EN 14470-2, EK5/AK4 09-10

Further TÜV testing (1):	DIN EN 14727
Further TÜV testing (2):	TRGS 510 Chapter 10
Added value mark of approval by TÜV:	High Quality
Declaration of conformity:	CE