

## Model: CLASSIC pro XL

Reference no.: 29-201265-053

Correct use: passive storage



|  |                        |
|--|------------------------|
| <b>Product group:</b>  | safety storage cabinet |
| <b>Fire resistance (FR):</b>   | Type 90                |
| <b>Catalogue page:</b>   | 48                     |
| <b>Doors can be opened with minimum effort, design:</b>                            | wing door              |
| <b>Door technology:</b>  | one-hand               |
| <b>In case of fire, automatic and blockage-free self-closing via thermocouple:</b> | yes                    |
| <b>Access control with cylinder lock:</b>  | ✓                      |
| <b>Enhanced ventilation concept - ventilation in every cabinet level:</b>          | ✓                      |
| <b>Visual inspection of ventilation cut-off flaps:</b>                             | ✓                      |
| <b>Outer width [mm]:</b>   | 1194 - (47.01 inch)    |
| <b>Outer depth [mm]:</b>   | 612 - (24.09 inch)     |
| <b>Outer height [mm]:</b>  | 2085 - (82.09 inch)    |
| <b>Base height [mm]:</b>   | 85                     |

|   |                            |
|---|----------------------------|
| <b>Easy transportation due to accessible base:</b>                                      | ✓                          |
| <b>Adjustable feet for level equalisation:</b>  | ✓                          |
| <b>Base version:</b>  | ToeKick                    |
| <b>Material outer carcass:</b>  | sheet steel, powder-coated |
| <b>Gross weight [kg]:</b>   | 471 - (1038.38 lbs)        |
| <b>Number of sides:</b>   | 1                          |
| <b>Inner width [mm]:</b>  | 979 - (38.54 inch)         |
| <b>Inner depth [mm]:</b>  | 469 - (18.46 inch)         |
| <b>Inner height [mm]:</b>   | 1697 - (66.81 inch)        |
| <b>Material inner carcass:</b>  | decor panels               |
| <b>Maximum volume of the largest individual container [l]:</b>                          | 30 - (7.93 gal)            |
| <b>Collection volume [l]:</b>   | 33 - (8.72 gal)            |
| <b>Shelf type:</b>  | pull-out shelf             |
| <b>Number of storage shelves:</b>   | 6                          |
| <b>Bottom tray interior:</b>  | bottom tray                |
| <b>Number of bottom trays:</b>  | 1                          |
| <b>Earthing connection according to TRGS 727 available:</b>                             | 1                          |
| <b>Number of earthing connections:</b>  | 2                          |
| <b>Exhaust air connection included:</b>   | NW 75/110                  |
| <b>Standing surface material:</b>   | sheet steel, powder-coated |
| <b>Load-bearing capacity per standing surface with uniformly distributed load [kg]:</b> | 60 - (132.28 lbs)          |

|  |                               |
|--|-------------------------------|
| <b>Adjustment height 1 left [mm]:</b>                          | 271 - (10.67 inch)            |
| <b>Adjustment height 2 left [mm]:</b>                          | 255 - (10.04 inch)            |
| <b>Adjustment height 3 [mm]:</b>                               | 255 - (10.04 inch)            |
| <b>Adjustment height 4 left [inch]:</b>                        | 255 - (10.04 inch)            |
| <b>Adjustment height 5 [mm]:</b>                               | 255 - (10.04 inch)            |
| <b>Adjustment height 6 [mm]:</b>                               | 265 - (10.43 inch)            |
| <b>Mark of approval by TÜV:</b>                                | GS mark                       |
| <b>Type-tested by recognised test institutes according to:</b> | DIN EN 14470-1                |
| <b>TÜV-tested according to:</b>                                | DIN EN 14470-1, EK5/AK4 09-10 |
| <b>Further TÜV testing (1):</b>                                | DIN EN 14727                  |
| <b>Further TÜV testing (2):</b>                                | TRGS 510 Annex 3              |
| <b>Added value mark of approval by TÜV:</b>                    | High Quality                  |
| <b>Declaration of conformity:</b>                              | CE                            |