

13.06.2018 11:22

Model: CLASSIC pro XL

Reference no.: 29-201267-051

Correct use: passive storage



| Product group: | safety storage cabinet |
|---|------------------------|
| Fire resistance (FR): | Туре 90 |
| Catalogue page: | 49 |
| Doors can be opened with minimum effort, design: | wing door |
| Door technology: | classical |
| In case of fire, automatic and blockage-free self- closing via thermocouple: | yes |
| Access control with cylinder lock: | ✓ |
| Enhanced ventilation concept - ventilation in every cabinet level: | ✓ |
| Visual inspection of ventilation cut-off flaps: | ✓ |
| Outer width [mm]: | 1194 - (47.01 inch) |



13.06.2018 11:22

| Outer depth [mm]: | 612 - (24.09 inch) |
|---|----------------------------|
| Outer height [mm]: | 2085 - (82.09 inch) |
| Base height [mm]: | 85 |
| Easy transportation due to accessible base: | ✓ |
| Adjustable feet for level equalisation: | \checkmark |
| Base version: | ToeKick |
| Material outer carcass: | sheet steel, powder-coated |
| Gross weight [kg]: | 470 - (1036.17 lbs) |
| Number of sides: | 1 |
| Inner width [mm]: | 979 - (38.54 inch) |
| Inner depth [mm]: | 469 - (18.46 inch) |
| Inner height [mm]: | 1697 - (66.81 inch) |
| Material inner carcass: | decor panels |
| Maximum volume of the largest individual container [l]: | 30 - (7.93 gal) |
| Collection volume [I]: | 33 - (8.72 gal) |
| Shelf type: | pull-out shelf |
| Number of storage shelves: | 4 |
| Bottom tray interior: | bottom tray |
| Number of bottom trays: | 1 |
| Earthing connection according to TRGS 727 available: | 1 |
| Number of earthing connections: | 2 |



13.06.2018 11:22

| Exhaust air connection included: | NW 75/110 |
|--|-------------------------------|
| Standing surface material: | sheet steel, powder-coated |
| Load-bearing capacity per standing surface with uniformly distributed load [kg]: | 60 - (132.28 lbs) |
| Adjustment height 1 left [mm]: | 399 - (15.71 inch) |
| Adjustment height 2 left [mm]: | 399 - (15.71 inch) |
| Adjustment height 3 [mm]: | 383 - (15.08 inch) |
| Adjustment height 4 left [inch]: | 377 - (14.84 inch) |
| Mark of approval by TÜV: | GS mark |
| Type-tested by recognised test institutes according to: | DIN EN 14470-1 |
| TÜV-tested according to: | DIN EN 14470-1, EK5/AK4 09-10 |
| Further TÜV testing (1): | DIN EN 14727 |
| Further TÜV testing (2): | TRGS 510 Annex 3 |
| Added value mark of approval by TÜV: | High Quality |
| Declaration of conformity: | CE |