

Model: CLASSIC standard L

Reference no.: 29-200965-030

Correct use: passive storage



Product group:	safety storage cabinet
Fire resistance (FR):	Type 90
Catalogue page:	45
Doors can be opened with minimum effort, design:	wing door
Door technology:	one-hand
In case of fire, automatic and blockage-free self-closing via thermocouple:	yes
Outer width [mm]:	894 - (35.20 inch)
Outer depth [mm]:	612 - (24.09 inch)
Outer height [mm]:	2085 - (82.09 inch)
Base height [mm]:	85
Gross weight [kg]:	365 - (804.69 lbs)
Number of sides:	1
Inner width [mm]:	798 - (31.42 inch)

Inner depth [mm]:	469 - (18.46 inch)
Inner height [mm]:	1697 - (66.81 inch)
Maximum volume of the largest individual container [l]:	20 - (5.28 gal)
Collection volume [l]:	22 - (5.81 gal)
Number of storage shelves:	4
Number of bottom trays:	1
Earthing connection according to TRGS 727 available:	1
Number of earthing connections:	2
Load-bearing capacity per standing surface with uniformly distributed load [kg]:	75 - (165.35 lbs)
Adjustment height 1 left [mm]:	398 - (15.67 inch)
Adjustment height 2 left [mm]:	398 - (15.67 inch)
Adjustment height 3 [mm]:	398 - (15.67 inch)
Adjustment height 4 left [inch]:	392 - (15.43 inch)
Mark of approval by TÜV:	GS mark
Type-tested by recognised test institutes according to:	DIN EN 14470-1
TÜV-tested according to:	DIN EN 14470-1, EK5/AK4 09-10
Further TÜV testing (1):	DIN EN 14727
Further TÜV testing (2):	TRGS 510 Annex 3
Added value mark of approval by TÜV:	High Quality
Declaration of conformity:	CE