

# Model: CLASSIC LINE

## Order number: 29-200667-030

Correct use: Passive storage



classical door technology (door handle), door hung right. for the storage of flammable liquids type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121 and DIN EN 16122, EK5/AK4 09-10:2009 and AfPS GS 2014: 01 PAK mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD construction and colour:

- outer carcass sheet steel, RAL 7035
- door sheet steel, RAL 1018
- inner carcass of decor panels, RAL 7035 fittings and features:
- door closes automatically in case of fire
- door remains open in every position
- cylinder lock for safe access
- bottom tray sheet steel, RAL 7035
- 4 storage shelves sheet steel, RAL 7035
- exhaust air connection socket on the cabinet roof
- visual inspection of the ventilation opening
- earthing connection on the cabinet roof
- interior fittings conductively connected with carcass
- adjustable foot for level adjustment
- set-back base, RAL 7015 Further technical information: [www.dueperthal.com](http://www.dueperthal.com)

|            |                             |
|------------|-----------------------------|
| Category:  | Type 90 - flammable liquids |
| Model size | M                           |
| Model type | STANDARD (storage shelves)  |

|   |                      |
|---|----------------------|
| Outer width [mm]:                         | 594                  |
| Outer depth [mm]:                         | 612                  |
| Outer height [mm]:                        | 2.085                |
| Net weight [kg]:                          | 265,00               |
| Number of storage levels                  | 4                    |
| Number of storage areas per storage level | 1                    |
| Door operation                            | classical technology |
| Door technology                           | wing door technology |