

14.06.2018 10:38

## Model: UTS ergo line M Reference no.: 29-060967-003

Correct use: passive storage



Product group:	safety storage cabinet
Fire resistance (FR):	Туре 90
Catalogue page:	119
Doors can be opened with minimum effort, design:	wing door
Door technology:	classical
In case of fire, automatic and blockage-free self- closing via thermocouple:	yes
Access control with cylinder lock:	✓
Enhanced ventilation concept - ventilation in every cabinet level:	✓
Visual inspection of ventilation cut-off flaps:	✓
Outer width [mm]:	888 - (34.96 inch)
Outer depth [mm]:	593 - (23.35 inch)
Outer height [mm]:	631 - (24.84 inch)
Base height [mm]:	35
Base version:	classical, with slots and floor extraction



14.06.2018 10:38

Material outer carcass:	sheet steel, powder-coated
Gross weight [kg]:	149 - (328.49 lbs)
Number of sides:	1
Inner width [mm]:	790 - (31.10 inch)
Inner depth [mm]:	463 - (18.23 inch)
Inner height [mm]:	480 - (18.90 inch)
Material inner carcass:	decor panels
Maximum volume of the largest individual container [l]:	16 - (4.23 gal)
Collection volume [I]:	18.1 - (4.78 gal)
Shelf type:	automatically extending pull-out tray
Number of storage shelves:	1
Perforated sheet interior:	perforated sheet insert
Number of perforated sheet inserts:	1
Earthing connection according to TRGS 727 available:	2
Number of earthing connections:	2
Exhaust air connection included:	NW 75
Standing surface material:	sheet steel, powder-coated
Load-bearing capacity per standing surface with uniformly distributed load [kg]:	45 - (99.21 lbs)
Adjustment height 1 left [mm]:	340 - (13.39 inch)
Mark of approval by TÜV:	GS mark



14.06.2018 10:38

Type-tested by recognised test institutes according to:	DIN EN 14470-1
TÜV-tested according to:	DIN EN 14470-1, EK5/AK4 09-10
Further TÜV testing (1):	DIN EN 14727
Further TÜV testing (2):	TRGS 510 Annex 3
Added value mark of approval by TÜV:	High Quality
Declaration of conformity:	CE