

13.06.2018 14:46

## Model: UTS ergo line ST Reference no.: 29-060669-001

Correct use: passive storage



Product group:	safety storage cabinet
Fire resistance (FR):	Туре 90
Catalogue page:	118
Doors can be opened with minimum effort, design:	wing door
Door technology:	push-to-open
Door hinge:	right
In case of fire, automatic and blockage-free self- closing via thermocouple:	yes
Access control with cylinder lock:	$\checkmark$
Enhanced ventilation concept - ventilation in every cabinet level:	$\checkmark$
Visual inspection of ventilation cut-off flaps:	✓
Outer width [mm]:	601 - (23.66 inch)
Outer depth [mm]:	593 - (23.35 inch)
Outer height [mm]:	631 - (24.84 inch)
Base height [mm]:	35



## Technical data sheet

13.06.2018 14:46

Base version:	classical, with slots and floor extraction
Material outer carcass:	sheet steel, powder-coated
Gross weight [kg]:	106 - (233.69 lbs)
Inner width [mm]:	503 - (19.80 inch)
Inner depth [mm]:	463 - (18.23 inch)
Inner height [mm]:	480 - (18.90 inch)
Material inner carcass:	decor panels
Maximum volume of the largest individual container [l]:	12 - (3.17 gal)
Collection volume [I]:	13.2 - (3.49 gal)
Bottom tray interior:	bottom tray
Number of bottom trays:	1
Perforated sheet interior:	perforated sheet insert
Number of perforated sheet inserts:	1
Earthing connection according to TRGS 727 available:	2
Number of earthing connections:	2
Exhaust air connection included:	NW 75
Standing surface material:	sheet steel, powder-coated
Load-bearing capacity per standing surface with uniformly distributed load [kg]:	60 - (132.28 lbs)
Adjustment height 1 left [mm]:	386 - (15.20 inch)
Mark of approval by TÜV:	GS mark



13.06.2018 14:46

Type-tested by recognised test institutes according to:	DIN EN 14470-1
TÜV-tested according to:	DIN EN 14470-1, EK5/AK4 09-10
Further TÜV testing (1):	DIN EN 14727
Further TÜV testing (2):	TRGS 510 Annex 3
Added value mark of approval by TÜV:	High Quality
Declaration of conformity:	CE