

stakpure OmniaPure

The specialist for H₂O pure type ASTM I

OmniaPure is a flexible system for the production of ultrapure water that fulfills the highest demands of analytical and life sciences laboratories.

The standardly integrated OptiFill dispenser is a jack-of-all-trades. It is so ergonomically shaped that it enables one-handed use, not only for system operation but also for the monitoring of all quality parameters.

You can decide on the best place for it in the laboratory, either mounted on a wall, standing on a bench or, to save valuable space, fitted in a base cabinet. The flexible dispensing/monitoring unit ensures very convenient and precise filling of laboratory vessels.

The combination of ultra-modern purification technologies in this system ensures need-filling and economical usage for any application.

stakpure

stakpure GmbH
Auf dem Kesseling 11
56414 Niederahr

Telefon: 02602 10673-0
Telefax: 02602 10673-200
info@stakpure.de
www.stakpure.de

Features

- ✓ Reliable ASTM I ultrapure water quality
- ✓ The standardly supplied OptiFill dispenser
 - enables one handed dispenser operation
 - is detachable and ergonomically shaped
 - can be turned and is height adjustable
- ✓ Programmable volume dispensing
- ✓ Simple and economical filter replacement
- ✓ Clear view of controls with graphic display
- ✓ Leak detector is standardly included
- ✓ Complete with integrated pressure reducer

NEW!



Standard system components

- √ Compact housing with easily accessible operating and service hood that enables simple replacement of spent materials in a few seconds
- √ Pressure reducer unit that is individually adjustable and purified water resistant
- √ Wide-range power supply unit with automatic voltage adjustment to 48 V that can be internationally used
- √ Quiet running long-life recirculation pump (< 40dB) for complete recirculation through all parts that contact media right up to the tip of the dispenser
- √ Integrated pretreatment set that protects against contaminants in the feed water – a guarantee for cleanliness and economy
- √ Ultrapure purification set for removal of inorganic substances and residual inorganic ions
- √ Quality rinse rinsing valve for complete disinfection of all parts that contact media as well as quality rinses in interval mode
- √ Multi-language microprocessor for the control and monitoring of all operating and performance parameters
- √ Dispenser with adapted microfiltration for sterile ultrapure water dispensing at the point-of-use

Microprocessor control

- √ Multi-lingual microprocessor control with graphics display and colour change from green to red when a fault message is given
- √ Individual setting possibilities for conductivity indication ($M\Omega \times cm$ or $\mu S/cm$) and language (German/English)
- √ Multi-level conductivity and temperature monitoring for pure and purified water, temperature compensation with continuously adjustable limiting value setting
- √ Automatic matching to an integrated reference resistance prior to each measurement ensures USP-conformity and high precision, plus possible switch-off of temperature compensation
- √ Leak monitoring with display of faults and automatic safety feedwater cut-off
- √ Automatic disinfection menu for easy and convenient disinfection of all parts that contact media for guaranteed microbial purity
- √ Exact and continuously variably dispensing from 0.1 to 60 liters allows convenient and reliable filling of laboratory vessels
- √ GLP conform data acquisition via an RS-232 interface with adjustable sending interval, date, real time clock and serial number

Feed water requirements

Water prepared by ion exchange, reverse osmosis, electrodeionisation or distillation

Feedwater temperature	+2°C to 35°
Feedwater pressure	0.1 to 6 bar
Input conductivity	< 100 µS/cm
TOC value	< 50 ppb

Type I ultrapure water

Ultrapure water conductivity	18.2 MΩ x cm \pm 0.055 µS/cm
Dispensing performance	up to 2 l/min.
Programmable volume dispensing	0.1 to 60 l
TOC-Wert	5-10 ppb*
Particle and bacterial content	< 1 CFU/ml
Typical applications	AAS, IC, ICP Preparation of buffer solutions

*Dependent on the feedwater and regular disinfection

Technical data

Ambient temperature	+2 to 35°C
Supply voltage	90-240 Volt / 50-60 Hz
Total connected load	0.1 kW
Connector inlet/rinse tube	d8 mm
Dimensions without dispenser	W 390 x D 375 x H 470 mm
Maximum dimensions with dispenser	W 390 x D 525 x H 720 mm
Weight	19 kg

Article number:

18200001 Main system OmniaPure

Consumables

19200002 Pretreatment cartridge OmniaPure
19200003 Ultra-pure water cartridge Omnia 055
19100300 Sterile filter capsule 0.2 µm
19102100 Bio filter capsule

Accessories

19200300 Wall holder Omnia
19200056 Disinfection kit Omnia
19200057 Disinfection solution 3pcs./pack