

stakpure Pure water system RO 200 easy

stakpure

Ready-to-connect RO system on stainless-steel frame. Multilingual microprocessor controller with LCD display for controlling and monitoring RO systems. Display of permeate conductivity, fully automatic rinsing cycles, potential-free fault reporting relay. Module-based capability of increasing capacity at a later stage.

stakpure GmbH
Im Bohnenhof 21
56414 Niederahr

Telefon: 02602 10673-0
Telefax: 02602 10673-200
info@stakpure.de
www.stakpure.de

Features

- √ Stainless-steel frame with PP- mounting plate
- √ Pre-filter unit
- √ High pressure pump
- √ Operating pressure gauge
- √ Feedwater pressure gauge
- √ Flow meter for permeate and concentrate
- √ 1 set control valve
- √ Inlet solenoid valve
- √ Flushing solenoid valve
- √ Feedwater Pressure switch
- √ High performance reverse osmosis module
- √ Pressure pipe
- √ Conductivity cell
- √ Complete piping with pipes out of PA, PP, POM and stainless steel material
- √ Microprocessor controller with LCD-display to control and display all relevant running parameters. Display of permeate conductivity, total running hours and potential free alarm contact.



Technical data

Pure water system for connection to softened (0°dH) or hardness-stabilized drinking water that complies with the German drinking water regulations

Blocking index	max. 3
Salt content	max. 2,000 mg/l
Free chlorine concentration	< 0.01 mg/l
Manganese content	< 0.05 mg/l
Iron content	< 0.05 mg/l
CO ₂ -content	max. 15 mg/l
SiO ₂ -content	max. 0.4 mg/l
pH-Range	4 to 11

Pure water values

Performance (at 10°C)	200 l/h
RO Membrane retention quota	> 99 % of salts, microorganisms and bacteria
WCF Rate	adjustable up to 75%

Limits and connections

Ambient temperature	5 to 40°C
Feedwater temperature	5 to 35°C
RO raw water pressure	2 to 6 bar
Maximum RO operating pressure	12 bar
Supply voltage	230 Volt / 50 Hz
Total connected load	0,60 kW
Inlet connector	DN 20
Outlet connector	DN 20
Width x depth x height	600 x 600 x 1600 mm
Approximate weight	100 kg

Article number:

15400200

Pure water system RO 200 EASY