

stakpure Water softener WEA 100 Duo 1

stakpure

Double water softener - volume controlled, for softening of iron and manganic free drinking water, according to Drinking Water Regulation, fully automatic 5-stage central control valve Type 9000 SXT with intelligent control electronics made of red brass with adapter for the second pressure vessel. 2 pressure tanks made of corrosion resistant fiberglass, including cation exchanger of highest quality. 1 brine tank with a perforated base and float valve (safety valve).

stakpure GmbH
Auf dem Kesseling 11
56414 Niederahr

Telefon: 02602 10673-0
Telefax: 02602 10673-200
info@stakpure.de
www.stakpure.de

Scope of delivery and technical data

2 Fiberglass pressure tank and filling with cation exchanger

Central control valve with 5 step regeneration program

Tank for dissolving salt and including float valve

Type	WEA 100 Duo 1
Capacity (at 10°dH . tap water)	100 m ³ x°dH
Flow rate	1,0 m ³ /h
Resin volume	2 x 25 Liter
Capacity of salt container	75 kg
Salt consumption	6,0 kg/reg.
Water consumption	0,25 m ³ /reg.
Operating pressure	2 to 6 bar
Max. water temperature	30°C
Max. ambient temperature	5 to 40°C
Power supply	220 V 50 Hz
Dimensions	W 1200 x D 500 x H 1200 mm
Piping connections	R1½
Article number	16128400



Abb.: Doppelenthärter mit Solebehälter

*Achtung Abb. zeigt Sensorgesteuerten Enthärter