

## stakpure Water softener WEA 200 Duo 1

stakpure

Double water softener - volume controlled, for softening of iron and manganic free drinking water, according to Drinking Water Regulation, fully automatic 5-stage central control valve Type 9000 SXT with intelligent control electronics made of red brass with adapter for the second pressure vessel. 2 pressure tanks made of corrosion resistant fiberglass, including cation exchanger of highest quality. 1 brine tank with a perforated base and float valve (safety valve).

stakpure GmbH  
Auf dem Kesseling 11  
56414 Niederahr

Telefon: 02602 10673-0  
Telefax: 02602 10673-200  
info@stakpure.de  
www.stakpure.de

### Scope of delivery and technical data

2 Fiberglass pressure tank and filling with cation exchanger

Central control valve with 5 step regeneration program

Tank for dissolving salt and including float valve

Type	WEA 200 Duo 1
Capacity (at 10°dH . tap water)	200 m <sup>3</sup> x°dH
Flow rate	2,0 m <sup>3</sup> /h
Resin volume	2 x 50 Liter
Capacity of salt container	150 kg
Salt consumption	12,0 kg/reg.
Water consumption	0,50 m <sup>3</sup> /reg.
Operating pressure	2 to 6 bar
Max. water temperature	30°C
Max. ambient temperature	5 to 40°C
Power supply	220 V 50 Hz
Dimensions	W 1300 x D 600 x H 1650 mm
Piping connections	R1½
Article number	16128600



Abb.: Doppelenthärter mit Solebehälter

\*Achtung Abb. zeigt Sensorgesteuerten Enthärter