

stakpure Water softener WEA 800 Duo 2

stakpure

Double water softener - volume controlled, for softening of iron and manganic free drinking water, according to Drinking Water Regulation, 2 x fully automatic 5-stage central control valve Type 2910 NXT made of red brass with water flow meter. 2 pressure tanks made of corrosion resistant fiberglass, including cation exchanger of highest quality. 1 brine tank with a perforated base and float valve (safety valve).

stakpure GmbH
Auf dem Kesseling 11
56414 Niederahr

Telefon: 02602 10673-0
Telefax: 02602 10673-200
info@stakpure.de
www.stakpure.de

Scope of delivery and technical data

2 Fiberglass pressure tank and filling with cation exchanger

2 Central control valve with 5 step regeneration program

Tank for dissolving salt and including float valve

Type	WEA 800 Duo 2
Capacity (at 10°dH . tap water)	800 m ³ x°dH
Flow rate	8,0 m ³ /h
Resin volume	2 x 200 Liter
Capacity of salt container	300 kg
Salt consumption	48,0 kg/reg.
Water consumption	2,0 m ³ /reg.
Operating pressure	2 to 6 bar
Max. water temperature	30°C
Max. ambient temperature	5 to 40°C
Power supply	220 V 50 Hz
Dimensions	W 2700 x D 950 x H 2200 mm
Piping connections	R 2+
Article number	16130600



Abb.: Doppelenthärter mit Solebehälter

*Achtung Abb. zeigt Sensorgesteuerten Enthärter