stakpure Water softener WEA 32 Compact

Completely automatic water softening unit that produces softened water with a residual hardness of 0.1° dH by means of the neutral exchange process with strong acid cation exchanger. Common salt is used for regeneration. Regeneration is carried out volume-dependently. Manual initiation of regeneration is also possible.

Scope of delivery and technical data

Fiberglass pressure tank and filling with cation exchanger Central control valve with 5 step regeneration program Container for dissolving salt Pre-assembled system ready for connection

| Туре | WEA 32 Compact |
|---------------------------------|--------------------------|
| Capacity (at 10°dH - tap water) | 32 m³x°dH |
| Flow rate | 0,32 m³/h |
| Resin volume | 8 liter |
| Capacity of salt container | 25 kg |
| Salt consumption | 1,92 kg/reg. |
| Water consumption | 0,08 m³/reg. |
| Operating pressure | 2 to 6 bar |
| Max. water temperature | 30°C |
| Max. ambient temperature | 5 to 40°C |
| Power supply | 220 V 50 Hz |
| Dimensions | W 310 x D 430 x H 660 mm |
| Piping connections | R1" |
| | |

16127200

Article number





stakpure GmbH Auf dem Kesseling 11 56414 Niederahr

Telefon: 02602 10673-0 Telefax: 02602 10673-200 info@stakpure.de www.stakpure.de