

MAGIO MX-Z Bridge mounted circulator

MAGIO bridge mounted circulators combine high temperature control performance with maximum flexibility. The adjustable bridge means that the circulators can be used with bath tanks up to a filling volume of 100 liters.

High resolution TFT touch display

The modern TFT touch display gives you all the important information at a glance. Three large, predefined main screens clearly display data and graphics with various application priorities. Menu navigation is self-explanatory, arranged by relevance to daily operations and easy to operate with the touch of a finger. The in-built help function provides detailed support in case of additional questions.



Product features

- Immersion depth of 200 mm (MX-Z) and 150 mm (MS-Z)
- Strong heating capacity of 3 kW (MX-Z) and 2 kW (MS-Z)
- Extendable stainless steel bridge from 33 to 68 cm
- Ideal for demanding external applications
- Simple control of complex applications
- Continuously adjustable, extremely powerful pressure / suction pump
- Flow rate 16 ... 31 l / min, pressure 0.24 ... 0.92 bar, suction 0.03 ... 0.4 bar
- Parts being in contact with the medium made of stainless steel
- Integrated programmer
- Integrated external Pt100 connection
- USB connection
- RS232 interface for online communication
- Ethernet
- analog interfaces (accessory)
- Connections for solenoid valve
- Large, high-resolution TFT touch display with multilingual user interface
- Class III (FL) according to DIN 12876-1
- Integrated pump connection M16×1

Technical data

Available voltage versions		Cooling	
Order No.	9 033 201	Cooling coil	integrated
Available voltage versions:			
9033201.33	200-230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9033201.33.chn	200-230V/50-60Hz (CN Plug)		

Other		Electronics	
Classification	Classification III (FL)	Interfaces	Ethernet, Modbus, RS232, RS485, Stakei, USB
IP Code	IP 20	External pt100 sensor connection	integrated
Pump function	Pressure Suction Pump	Integrated programmer	8x60 steps
Pump type	Immersion Pump	Temperature control	ICC
User Interface Language	Chinese, Czech, Dutch, English, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Turkish	Absolute temperature calibration	10 Point Calibration
		Temperature display	7" TFT Touchscreen
		Temperature setting	Touchscreen
		Electronic Timer h:min	00:00 ... 99:59
Dimensions and volumes		Temperature values	
Usable immersion depth cm	20	Setting the resolution of the temperature display °C	0.01
Weight kg	7.6	Working temperature range °C ¹	+20 ... +300
Dimensions cm (W x L x H)	34 x 19 x 41	Temperature stability °C	±0.01
Pump connections	M16x1 male	Ambient temperature °C ²	+5 ... +40
		Setting the resolution of the temperature display °C	0.01
		¹ Bath fluids from JULABO available for working temperatures up to +250°C. For higher temperatures consider closed systems like Forte HT. ² For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.	

Included in delivery

2 Barbed fittings for tubing 8 and 12 mm ID. (Pump connections M16x1 male)

All Benefits



Intelligent temperature control.

Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



Many interfaces.

Straight-forward remote control, data management, and integration into process structures. USB, Ethernet, RS232, SD card, and alarm off are permanently integrated. Further interfaces available as accessories.



Touch display. Perfect operation.

With the touch display, the user always has an overview of all values and functions. The intuitive and multilingual menu structure enables perfect control.



Maximum safety.

Classification III according to DIN12876-1 enables safe operation, even with flammable fluids. Automatic switch-off in the event of high temperature or low liquid level.



Space saving. Free up space.

Place your JULABO Circulator right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



Multi-lingual.

Operation in multiple languages.



Programmer. Integrated.
The integrated internal programmer makes it possible to automatically run temperature time profiles.



Analog I/O.
Analog interfaces for integration into process control systems (optional).



Temperature. Under control.
External Pt100 sensor connection for precise measurement and control directly in the external application.



Fill level. Monitored.
Fill level indicator on the display for heat-transfer liquid.



Process stability.
Early warning - visual and acoustic - of critical states increases process stability.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



Stable. Mobile.
Rubber feet keep JULABO Circulators standing firm. Larger and more powerful units also have integrated rollers for easy handling.



Energy-saving.
The high-quality insulation of all relevant components saves energy.



Everything made of stainless steel.
Quality and material compatibility at the highest level. All parts in contact with the medium are entirely made of stainless steel.



Most powerful pump.
The integrated pressure/suction pump with performance values of 0.9 bar and -0.4 bar is the most powerful in its class and continuously adjustable.



Wide range.
Refrigerated and heating circulator in various combinations, circulator in various sizes. Maximum flexibility through a large selection of accessories.



Condensation protection.
Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.



Connection. Easy.
Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



Highest measuring accuracy
'Absolute Temperature Calibration' for manual compensation of a temperature difference, 10-point calibration



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.