CORIO CD-BT27 Heating circulator with open bath and transparent bath tanks

The open heating bath circulators of the new CORIO series feature highquality transparent bath tanks and pump connections.


Product features

- Bright, white, easy to read display
- Very quiet
- easy switching between internal and external circulation
- USB connection
- Class III (FL) according to DIN 12876-1
- For internal and external applications



Julabo

Heat-up time



Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
Heating capacity kW	2	
Viscosity max. cSt	50	
Pump capacity flow rate I/min	15	
Pump capacity flow pressure bar	0.35	
Power consumption A	10	

Technical data

Available voltage versions Bath			
Order No.	9 012 327	Bath tank	Polycarbonat
Available voltage versions:		Bath cover	accessory
9012327.01	100V/50-60Hz (Nema N5-15 Plug)	Usable bath opening cm (W x L / D)	30 x 35 / 20



9012327.02	115V/60Hz (Nema N5-15 Plug)
9012327.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)
9012327.03.chn	230V/50Hz (CN Plug)
9012327.04	230V/50Hz (UK Plug Type BS1363A)
9012327.05	230V/50Hz (CH Plug Type SEV 1011)
9012327.13	230V/60Hz (Nema N5-15 Plug)

Cooling		Other	
Cooling coil	accessory	Classification	Classification III (FL)
		IP Code	IP 21
		Pump function	Pressure Pump
		Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Interfaces	USB	Weight kg	8.1
Temperature control	PID1	Barbed fittings inner diameter	8/12 mm
Absolute temperature calibration	1 Point Calibration	Dimensions cm (W × L × H)	38 x 58 x 43
Temperature display	LED	Filling volume I	20 27
Temperature setting	Keypad	Pump connections	M16x1 male
Temperature values		Included in delivery	
Setting the resolution of the temperature display °C	0.1	2 Barbed fittings for tubing 8 and 12 mm ID. (Pump connections M16x1 male)	
Working temperature range °C	+20 +100		
Temperature stability °C	±0.03		
Ambient temperature °C	+5 +40		
Temperature display resolution °C	0.01 0.1		

For applications near or below ambient temperature: use a cooling coil or JULABO immersion cooler.

All Benefits



Brilliant.

Very bright display makes it easy to read even from a distance.



Timer. Integrated.

CORIO circulators include an integrated timer function. When the set time has elapsed, a signal sounds and the device switches off. Setting range: 0 ... 999 minutes.



Exact.

You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO precise and perfect.



Switch on. And off you go. Intelligent operating concept. Ready for operation with just a few quick and easy steps.



Everything at the front. All operating controls and safety functions are accessed easily and comfortably from the front.



Locked in. The lockable power plug guarantees safe connection. More process safety.





Connection. Easy.

Inclined pump connections (M16×1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



Connectivity. Remote control made easy. CORIO CD circulators feature a USB connection.



ATC. Absolute Temperature Calibration, 1-point calibration (CD).



Internal. External.

The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.



Modern. Reliable.

High-grade components in every JULABO Circulator – platinum sensors, proven motor technology, CAN-Bus communication and much more.



Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



Early warning system for low liquid level Maximum safety for applications, optical and audible alarm, allows user to refill bath fluid before the unit shuts down

100% Checked.



100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.

Green technology.

Development consistently applied environmentally friendly materials and technologies.



Made in

German

JULABO. Quality.

Highest standards of quality for a long product life.

8 3 8 8 8 8 8 8 8 8 8

Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Stable.

Rubber feet allow for a secured footing of your CORIO to prevent damage to your laboratory equipment.