

SL-14K HighTech SL calibration bath

JULABO calibration baths are ideal for high precision calibration of sensors, measuring instruments, thermometers, etc. The instruments are certified for application in DKD laboratories and according to the requirements specified by DIN EN ISO 9001:2000.

Product features

- LCD DIALOG DISPLAY backlit for convenient interactive operation
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- Integrated programmer for 6 x 60 program steps
- Highest temperature stability to ±0.005 °C (±0.02 °C at +200 °C)
- Temperature uniformity better than ±0.01 °C
- Optional Pt100 sensor for reference temperature measurements
- Temperature chamber with overflow at maximum liquid level



Technical data

Available voltage versions		Cooling	
Order No.	9 352 514	Cooling coil	integrated
Available voltage versions:			
9352514.33	230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)		

Plug Type F)			
Bath		Other	
Bath tank	Stainless steel	Classification	Classification III (FL)
Bath cover	integrated	IP Code	IP 21
Usable bath opening cm (W x L / D)	12	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Interfaces	Profibus optional	Usable immersion depth cm	31
External pt100 sensor connection	integrated	Weight kg	20
Integrated programmer	6x60 steps	Dimensions cm $(W \times L \times H)$	22 x 46 x 61
Temperature control	ICC	Filling volume I	14
Absolute temperature calibration	3 Point Calibration		
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values		Included in delivery	

Temperature values				
Working temperature range °C	+50 +300			
Temperature stability °C	±0.005			
Ambient temperature °C ¹	+5 +40			
Setting the resolution of the temperature display °C	0.01			

Included in delivery

Including bath cover with seven openings



All Benefits



For flammable bath fluid

Classification III (FL) according to DIN 12876-1



ATC3. Calibration.

'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.

Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity

'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Early warning system for high/low temperature limits

Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Energy saving cooling

Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Connection of additional equipment

Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Clever pump system

Reliable and consistent pump capacity, electronically adjustable pump stages



Control of the external application

External Pt100 sensor connection for precise measurement and control directly in the external application



Condensation and ice protection

A heated cover plate prevents condensation or ice build-up in the bath



100% Checked.

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.

Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.

Highest standards of quality for a long product life.



Ouick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.

¹ Depending on the ambient temperature and the bath fluid used, it may be necessary to use the cooling coil for temperature applications around +50 °C.