

PLW 8617 [EL TH RT]

Laboratory washer

– single door, w/ pre-heating and recycling tank, 1150 mm wide, 351 l usable cap.



- Capacity/cycle, e.g. 216 laboratory flasks, 588 vials or 294 pipettes
- Short cycle times thanks to pre-heated demineralised water
- Up to 60 % less water consumption based on the load *
- Environmentally friendly thanks to recycling tank
- Flexible and simple – modular load carriers & EasyLoad system
- Efficient – strong pump power with the variable-speed pump
- Reliable results – spray arm monitoring and conductivity meter

* e.g. 60 % saving with 100 ml laboratory bottles in Universal Max programme compared to Lab Universal programme for PG 8527

EAN: 4002516456674 / Material number: 11842860 /
Old Material Number: 62861704EXP

Construction type and version	
Construction type	Freestanding, 1 glass vertical sliding door
Type of heating	Electricity
Front/back	Stainless Steel
Side panels	Stainless steel
Single/multiple installations	•
Loading with mobile units	•
Electric door lock	•
Buzzer, acoustic signal at end of programme	•
Service-friendly design	•
Application	
Suitable for laboratories	•
Suitable for industrial applications	•
Capacity	
Narrow-necked glassware per cycle [number]	216
Test tubes per cycle [number]	588
Laboratory flasks per cycle [number]	216
Pipettes per cycle [number]	294
Performance data	
Circulation pump, Qmax in l/min	400
Additional circulation pump for load carrier – direct coupling, Qmax in l/min	600
Variable-speed pump	•
Wash cabinet usable capacity in l	351
Tested operating hours	15000
Service life in wash cycles	20000
Control system	
Control type	PST 20
Programme selection	Full-touch colour display
Programmability	programmable
Programmes [number]	30
Free programme positions [number]	170
Automatic programme restart	•
Time left display	•
Programme sequence display	•
Status display via chamber lighting	•
Selectable display languages	•
Standard electrical connection	
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	18,00
Total rated load in kW	20,00
Fuse rating in A	32-35
Water connection/drainage	
Cold water [number]	2
Hot water [number]	1
DI water [number]	2
Required flow pressure in kPa	200-1000

PLW 8617 [EL TH RT]

Laboratory washer

– single door, w/ pre-heating and recycling tank, 1150 mm wide, 351 l usable cap.



EAN: 4002516456674 / Material number: 11842860 /

Old Material Number: 62861704EXP

Maximum water hardness (cold water/hot water) in mmol/l	0,71
Drain valve [DN]	50
Drain pump (optional)	•
Compressed air connection	
Compressed air connection, technical [number]	1
Required compressed air, technical, in kPa	600-800
Drying unit	
Drying unit heating type	Electricity
Air throughput in m ³ /h	250
Time setting in 1-minute increments	1-240
HEPA filter class	H13
HEPA filter filtration efficiency (DIN EN 1822) in %	99,95
Electric heater rating in kW	8,00
Dimensions and weight	
External dimensions, net height in mm	1670
External dimensions, net width in mm	1150
External dimensions, net depth in mm	990
External dimensions incl. plinth/floor tray and top-box panelling, height in mm	2495
External dimensions, gross height in mm	1960
External dimensions, gross width in mm	1250
External dimensions, gross depth in mm	1130
Wash cabinet, height in mm	675
Wash cabinet, width in mm	650
Wash cabinet, depth in mm	800
Rack height above floor in mm	850
Net weight in kg	407
Gross weight in kg	419
Maximum floor load in N/m ²	8000
Emissions data	
Sound pressure LpA in cleaning and drying according to DIN EN ISO 11201	<65 dB(A) re 20 µPa
Programmes	
Thermal disinfection	•
Laboratory glassware reprocessing	•
Plastics	•
Oil soiling	•
Industrial parts cleaning	•
Features	
2 integrated diaphragm dispenser pumps for liquid media	•
Additional integrated dispenser pumps	4
Heated tank for pre-heating DI water	•
Recycling tank	•
Steam condenser (optional)	•
Volume flow control	•
Spray arm monitoring	•
Conductivity monitoring	•
Interface for process documentation	•
Multi-component filter system	•

PLW 8617 [EL TH RT]

Laboratory washer

– single door, w/ pre-heating and recycling tank, 1150 mm wide, 351 l usable cap.



EAN: 4002516456674 / Material number: 11842860 /

Old Material Number: 62861704EXP

Micro-fine filter	•
Load carrier – direct coupling	•
Integrated hot air drying (optional)	•
Integrated printer for process documentation (optional)	•
Heater elements outside wash cabinet	•
EasyLoad	•
Setting options for process chemicals (4 x 10 l)	•
Wash cabinet made from high-quality stainless steel (1.4404/316L)	•
Plinth, on wheels (optional)	•
Drain water cooling (optional)	•
Multi-coloured chamber lighting	•
Modular basket design	•
Option of using existing load carriers	•
Connection options	
Ethernet interface	•
External dispensing modules	•
USB interface	•
Central dispensing	•
Peak-load negotiation / energy management	•
Standards, test certificates and symbols	
CE	•
VDE (electrical safety)	•
EN 61010-2-040	•
Machinery Directive 2006/42/EC	•