

stakpure water softener

WEA 72 Duo 1 compact

Double system, volume-controlled, for softening drinking water that is free of iron and manganese, in accordance with the Drinking Water Ordinance, fully automatic 5-stage central control valve type Fleck 9100 SXT with intelligent control electronics made of gunmetal/plastic with an adapter for the second pressure vessel. 2 pressure tanks made of corrosion-resistant GRP, including a high-quality cation exchanger. 1 brine tank with a sieve floor and float valve (safety valve).

Design and scope of delivery

1 cabinet tank with brine tank and float valve

2 GRP pressure tanks with cation exchanger

→Fully automatic central control valve

Technical data

Type	WEA 72 Duo 1 compact
Capacity	2x 72 m³x°dH
Nominal flow rate	1.1 m³/h
Operating pressure	3 to 6 bar
Max. water temperature	40°C
Max. ambient temperature	5 to 40°C
Electrical connection	230 V 50 Hz
Dimensions of housing approx.	W 350 x D 460 x H 1180 mm
Water connection	R 1"
Order no.	16128300

stakpure

stakpure GmbH
Auf dem Kesseling 11
56414 Niederahr

Telefon: 02602 10673-0
Telefax: 02602 10673-200
info@stakpure.de
www.stakpure.de

